

## SAAMI DROP TEST

TEST TITLE \_\_\_\_\_

REPORT # \_\_\_\_\_ W.O.# \_\_\_\_\_ DATE \_\_\_\_\_

MODEL XP100R SERIAL# B75320 35 TRIGGER PULL (LBS.) 3.5

COMMENTS \_\_\_\_\_

SAAMI SPEC: JAR OFF TEST IS 12 INCH DROP, WITH SAFE IN "OFF" POSITION, MEASURED FROM THE LOWEST POINT OF GUN.  
ONE DROP IN EACH OF THE FOLLOWING POSITIONS AGAINST A 1 INCH, 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE.

12 INCH DROP (SAFE OFF)

|                                  |           |
|----------------------------------|-----------|
| BARREL VERTICAL, MUZZLE UP       | <u>OK</u> |
| BARREL VERTICAL, MUZZLE DOWN     | <u>OK</u> |
| BARREL HORIZONTAL, BOTTOM DOWN   | <u>OK</u> |
| BARREL HORIZONTAL, BOTTOM UP     | <u>OK</u> |
| BARREL HORIZONTAL, LEFT SIDE UP  | <u>OK</u> |
| BARREL HORIZONTAL, RIGHT SIDE UP | <u>OK</u> |

48 INCH DROP (SAFE ON)NOTE: DROP IS 48 INCHES FROM THE CENTER OF GRAVITY OF THE FIREARM

|                                  |           |
|----------------------------------|-----------|
| BARREL VERTICAL, MUZZLE UP       | <u>OK</u> |
| BARREL VERTICAL, MUZZLE DOWN     | <u>OK</u> |
| BARREL HORIZONTAL, BOTTOM DOWN   | <u>OK</u> |
| BARREL HORIZONTAL, BOTTOM UP     | <u>OK</u> |
| BARREL HORIZONTAL, LEFT SIDE UP  | <u>OK</u> |
| BARREL HORIZONTAL, RIGHT SIDE UP | <u>OK</u> |

## "ROTATION TEST"

BUTT ON MAT, LET FIREARM FALL TO LEFT AND RIGHT

|               |           |
|---------------|-----------|
| LEFT SIDE UP  | <u>OK</u> |
| RIGHT SIDE UP | <u>OK</u> |