

B-

DO NOT SCALE THIS DRAWING; WORK TO FIGURES
UNLESS OTHERWISE NOTED.

TOLERANCES ON DECIMAL DIMENSIONS ARE:

- 1 PLACE .1 IN. TOLERANCE $\pm .015$
- 2 PLACE .01 IN. TOLERANCE $\pm .010$
- 3 PLACE .001 IN. TOLERANCE $\pm .005$

ON FRACTIONAL DIMENSIONS $\pm 1/64$
ON ANGULAR DIMENSIONS $\pm 00^{\circ} 30'$

FINISHES ARE DESIGNATED BY ROOT MEAN
SQUARE (R.M.S.) MICRO-INCH ROUGHNESS
VALUES AND ARE THE MAXIMUM ROUGHNESS
ACCEPTABLE, UNLESS OTHERWISE SPECIFIED.

FINISH ROUGHNESS TO BE $125 \sqrt{V}$ OR BETTER.

FINISH ROUGHNESS TO BE $\sqrt{125}$ OR BETTER.

MATERIAL _____
HEAT TREAT _____
HARDNESS _____
COLOR _____
HEAT TREAT AND COLOR TO BE DONE BY
REMINGTON

[illegible]

AUTHORIZED
4-17-91
Process Engineering

V FILENAME - RES.700.LB556.17X64-CHAMBER.LLW

**CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON**

R2519770
BARBER - PRESALE R 0118782