

CALSONIC

FROM: CALSONIC

TO:

OCT 1, 1991 2:22PM

PAGE 1 OF 7

CALSONIC

CALSONIC TECHNICAL CENTER

☒ CTC - ARIZONA
10232 S. 51st ST.
PHOENIX, AZ 85044
(602) 253-6185
FAX (602) 253-0048

☐ CTC - CALIFORNIA
NINE HOLLAND
IRVINE, CA 92718
(714) 855-3000
FAX (714) 951-1827

☐ CTC - MICHIGAN
ONE HERITAGE DRIVE, SUITE 600
SOUTHGATE, MI 48195
(313) 282-7700
FAX (313) 282-2640

☐ CTC - TENNESSEE
305 STANLEY BLVD.
SHELBYVILLE, TN 37180
(615) 684-9432
FAX (615) 684-4490

DATE

9/30/91

TO:

M. KEENEY

COMPANY:

RAMINGTON

FAX NO.: 895-4107 DEPT.:

315-894-9961

EXT 226

FROM:

D. KEENEY

SUBJECT:

REINFORCED MATERIALS FROM "FORMULAS FOR STRESS AND STRAIN"

By Raymond J. Roark.

ALSO, YOU NEED TO CONSIDER STRESS CONCENTRATION AT CORNERS
OF TUB/LUG JOINTS. ROUND VS. SQUARE HOLE IN TUB, WOULD
REDUCE STRESS CONCENTRATION.

FOR BRITTLE CONTINU MATERIALS, CONTACT MEASUREMENTS
GROUP, INC., PO BOX 27777, RALEIGH, NORTH CAROLINA 27611.
PHONE NO. 919-365-3800. NAME OF THEIR STRESSCOAT
PRODUCT IS "TENS-LAC".

[Signature]

MIKE: I SENT THIS YESTERDAY TO 315-894-9961 EXT. 452
(THE TELEPHONE OPERATOR TOLD ME TO USE X-452).