

Report# 920431

15

Work Order# 481167

MODEL 700 STAINLESS STEEL, DESIGN ACCEPTANCE

APPENDIX B

ACCURACY

CAL.	SERIAL#	Group	0 rounds	2000 rds.	4000 rds.
300 Win. Mag.	C6678188	1	2.28	1.31	2.23
		2	1.97	1.58	3.25
		3	2.65	1.55	2.55
		AVG.	2.30	1.48	2.68
300 Win. Mag.	C6671714	1	2.40	1.67	2.08
		2	1.49	1.67	1.73
		3	1.32	1.37	2.37
		AVG.	1.74	1.57	2.06
7mm Wby. Mag.	C6678201	1	1.70	1.61	1.47
		2	1.31	1.60	1.67
		3	1.42	.72	1.81
		AVG.	1.48	1.31	1.65
7mm Wby. Mag.	C6678174	1	1.68	1.89	2.81
		2	2.30	1.86	2.76
		3	2.40	1.45	3.97
		AVG.	2.13	1.73	3.18
338 Win. Mag.	C6671720	1	1.97	1.65	1.67
		2	2.19	1.60	2.61
		3	3.30	1.04	1.56
		AVG.	2.49	1.43	1.95
338 Win. Mag.	C6678193	1	2.21	.83	2.70
		2	1.31	1.30	1.74
		3	2.92	1.12	2.35
		AVG.	2.15	1.08	2.26
7mm Rem. Mag.	C6678181	1	1.95	1.35	2.92
		2	1.13	.67	4.15
		3	1.58	2.14	3.19
		AVG.	1.55	1.38	3.42*
7mm Rem. mag.	C6678192	1	1.21	3.01	1.61
		2	2.89	.81	1.73
		3	2.52	1.48	1.27
		AVG.	2.20	1.76	1.54

* Out of zero round specification of 2.7 inches.