

6.93 WAW

N BAR FIRE CONTROL

TRIGGER RETRACTION UPON PARTIAL
PULL IS IMPORTANT:

- M200 RELIES ON POWDERAGE
SPRING; NOT MAINSPRING

* THIS WOULD BE A CONCERN IN
ANY SYSTEM WHERE FRICTION ~~CAN~~
FORCE OPPOSING TRIGGER PULL IS GREATER
THAN THE SPRING COMPONENT OPPOSING
TRIGGER PULL.

GUNS COLT SAVER
 REL BOLT LOCK
 TOGGLE TRIGGS

CHANGE S. U. F. SEQUENCE OF 3 POS SAFETY

U S F

COW RATE SPRING

BOLT LOCK INDEPENDENT OF SAFETY -
 LOCKED WHEN BOLT CUSSED. DISABLED BY F. DN FALL
 OR OVER-RIDE BUTTON.

TRIGGER BLOCK SAFETY: HOW TO MAINTAIN
 TRIGGER/SAFETY RELATIONSHIP WHEN ADJUSTING
 TRIGGER/SEAR RELATIONSHIP.

TRIGGER BLOCK

FIRST THING TO BE BLOCKED (F → S)
 CARRIED INTO SEM SUPPORT POSITION OR SAFETY WHEN MORE
 LAST THING TO BE FREED (S → F)

F → S

CAM TRIGGER INTO SUPPORT POSITION
 BLOCK IT THERE
 CAM SEAR UP OFF OF TRIGGER
 CAM F.P BACK

S TO F | RELEASE SEAR TO CONTACT TRIGGER
 UNBLOCK TRIGGER

INSERT TRIGGER & SEAL SUPPORT SURFACE
BROWING BED USE DULOW SCREEN WITH STEEL
PANI INSERTED INTO THE TRIGGER.