

MDK
08/09/93

NBAR FEATURES:

RECBAR:

1. INTERGAL BARREL AND RECEIVER
2. FORGED BARREL AND RECEIVER
3. 5R RIFLING
4. FORWARD LOCKING, THREE LUG
(67 DEG. BOLT ROT.)
5. ACTION LENGTH .5" SHORTER THAN M/700
(RIGID)
6. GREATER LOCKING STRENGTH THAN M/700
(BEARING AND SHEAR AREA)
7. COMMON BARREL CONTOUR (MAG AND REG)
8. DETACHABLE MAG. BOX, STAGGERED BOX/INLINE FEED
9. COMMON SCOPE MOUNTING SURFACES
10. REMINGTON ONE PIECE SCOPE MOUNTS RADIALY FASTENED
TO RECEIVER

BOLT ASSEMBLY:

1. ENCLOSED BOLT SHROUD
2. CLAW EXTRACTOR
3. COCKING INDICATOR
4. ENCLOSED BOLT PLUG ??????
5. FIELD STRIPPABLE

(2)

TRIGGER ASSEMBLY:

1. TWO POSITION SAFETY WITH RELEASABLE BOLT LOCK
2. CUSTOMER ADJUSTABLE TRIGGER PULL ABOVE SAFE LIMIT
3. WIDE TRIGGER

STOCK ASSEMBLY:

1. ALUMINUM RECOIL/BEDDING INSERT EPOXIED OR MOLDED INTO STOCK
(FRONT AND REAR ALUMINUM BEDDING)
2. FUTURISTIC SYNTHETIC STOCK WITH INSERTABLE PADS
3. CLASSIC WALNUT STOCK

LOCK TIME :

~~30%~~ 30% REDUCTION IN LOCK TIME FROM m/700
(3.0 ms → 2.1 ms)
5-10% QUICKER THAN m/788 (788 = 2.3 ms)
→ that is for long action !!
→ short action NBAR possibly under 2 ms