

WAW

8.10.93

IF BOLT LOCK/BOLT STOP ARE
COMMON/INTER-RELATED PARTS,
THEN IT SHOULD BE DONE IN A
WAY THAT USER CAN ELECT
NOT TO HAVE BOLT ~~LOCK~~ LOCK
FUNCTION BUT RETAIN BOLT
STOP FUNCTION.

- @ FACTORY
- @ GUNSMITH
- @ SELF

BEST WAY WOULD ~~XXX~~
INVOLVE ^{NOT} REMOVING A
PART

- COST/MISPLACED
- THEN DIFFICULT TO
RESTORE OTHER MODE.

FOR MINIMUM (FLOOR) ON TRIGGER
PULL :

- DUAL SPRING SYSTEM

- 1 FIXED MINIMUM PERMANENT INSTALLATION
@ ASS'T.

1 ADDITIVE FOR ADJUSTMENT

- SINGLE SPRING WITH,
MINIMUM PRELOAD MAINTAINED
WHEN ADJUSTMENT IS COMPLETED
TO MINIMUM EXTREME.

BROWNING BBA

- ACCESSIBLE WITHOUT
RIFLE DISASSEMBLY
- ACCESSIBLE ONLY WITH
RIFLE DISASSEMBLY.