

R2521555
BARBER - PRESALE R 0120567

MAX. ECCENTRICITY .002
TOTAL DIAL READING
.004.

CTIONS				
LET.	WAS	REFERENCE	BY	DATE
23	REDRAWN	4671	GR	5-3-66
24	AF-7043	"	GR	5-3-66
25	ADD USE: 6043	5120	1/5	1/2/66
26	ADDED USE	6479	DD	3-14-66
27	ADD USE 660	6664	1/5	1/10-16
28	ADD MONTHLY USE 600	8444	Re	3-11-70
29	ADDED	11204	VB	3-15-80
30	WAS 035-090	1164	DB	8-27-94
31	WAS - 030	"	"	"
32	ADD USE 7217	11667	"	12/8/92

FOR BLANK DRAWING
SEE B-91918

DIM.	MANUFACTURING DIM.	DIM. AFTER HEAT TREAT
A	1245 - 1225	123 - 125*

* NOTE

THIS DIA. MUST PASS THRU
A .125 DIA. RING GAGE FREELY

THIS DRAWING OR INFORMATION IS
PROPRIETARY INFORMATION TO THE
REMINGTON ARMS COMPANY, INC.

RECOMMENDED MATERIAL AND HEAT TREAT

003-006 CASE
NITRE, BLACK
HEAT TREAT AND COLOR TO BE DONE BY REMINGTON

B-17043

22	7LWT	SAFETY PIVOT PIN	1	P.L.
23	MOHAWK 600N	SAFETY PIVOT PIN	1	C-26795
24	660	SAFETY PIVOT PIN	1	
25	104VME	SAFETY PIVOT PIN	1	D-2634
26	40XB IFR SAFE	SAFETY PIVOT PIN 0.02 TRIGGER	1	D-27565
27	40X-8	SAFETY PIVOT PIN	1	D-27580
	600	SAFETY PIVOT PIN		P.L.
	XPT00	SAFETY PIVOT PIN		P.L.
	700BDL	SAFETY PIVOT PIN		D-26345
	700ARD	SAFETY PIVOT PIN		D-26345
	40XCF	SAFETY PIVOT PIN		P.L.
	725	SAFETY PIVOT PIN		D-24573
	40-X	SAFETY PIVOT PIN		P.L.
	722	SAFETY PIVOT PIN		D-170367
	721	SAFETY PIVOT PIN		D-170367
MODEL		PART USE		QUAN.
DES'D BY DATE		DRAWN BY DATE		CHECK BY DATE
		E. REED 4/11/62		APPR. BY DATE VAL 5/15/62
TITLE				
PIN				
NUMBER		SCALE	SUPERSEDES - REFERENCE	
B-17043		3:1	A-17043	
REMINGTON ARMS CO. INC.				
RESEARCH & DEV. DEPT.				