

0062E-B

DO NOT SCALE THIS DRAWING. WORK TO FIGURES
UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:
1 PLACE (.1) — TOLERANCE ± .015
2 PLACE (.01) — TOLERANCE ± .010
3 PLACE (.001) — TOLERANCE ± .005
4 ON FRACTIONAL DIMENSIONS ± 1/64
5 ON ANGULAR DIMENSIONS ± 00° - 30'
FINISHES ARE DESIGNATED BY ROOT MEAN
SQUARE (R.M.S.) MICRO-INCH ROUGHNESS
VALUES AND ARE THE MAXIMUM ROUGHNESS
ACCEPTABLE UNLESS OTHERWISE SPECIFIED.
FINISH ROUGHNESS TO BE "12" OR BETTER.

RECOMMENDED MATERIAL AND HEAT TREAT

MATERIAL CALCO-NIURIDE
HEAT TREAT P15N-88-92
HARDNESS P15N-88-92
COLOR P. OIL
HEAT TREAT AND COLOR TO BE DONE BY
REMINGTON DEC 1947

ALTERATIONS			
ALT.	WAS	REF.	BY

BUTTON
C-14578

PROJECTION WELD

SAFETY
C-90556

100 L.H.		SAFETY ASSY.	
MODEL PARTNO.		PART USE	
DES. BY DATE	CHK. BY DATE	APP. BY DATE	APP. BY DATE
TITLE SAFETY ASSY.			
NUMBER	SCALE	SUPPLY TO	REFERENCE
B-52900	AS1		
REMINGTON ARMS CO. INC. ELION R. PARCET DIV.			