

THIS DRAWING OR INFORMATION IS
PROPRIETARY INFORMATION TO THE
REMINGTON ARMS COMPANY, INC.

DO NOT SCALE THIS DRAWING: WORK TO FIGURES
UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:
1 PLACE (.1) — TOLERANCE $\pm .015$
2 PLACE (.01) — TOLERANCE $\pm .010$
3 PLACE (.001) — TOLERANCE $\pm .005$
& ON FRACTIONAL DIMENSIONS $\pm 1/160$
& ON ANGULAR DIMENSIONS $\pm 30' - 30''$
FINISHES ARE DESIGNATED BY ROOT MEAN
SQUARE (R. M. S.) MICRO-INCH ROUGHNESS
VALUES AND ARE THE MAXIMUM ROUGHNESS
ACCEPTABLE UNLESS OTHERWISE SPECIFIED.
FINISH ROUGHNESS TO BE 1.25 OR BETTER.

RECOMMENDED MATERIAL AND HEAT TREAT

MATERIAL _____
HEAT TREAT _____
HARDNESS _____
COLOR _____
HEAT TREAT AND COLOR TO BE DONE BY
REMINGTON

ALTERATIONS

ALT.	WAS	REV.	BY	DATE

PART NO.	BOLT PLUG	FIRING PIN	F. PIN CROSS PIN	F. PIN HEAD	MAINS PRING
100340	92710	100331	17022	92709	
100341	"	100330	"	"	

MODEL	100341	FIRING PIN ASSEMBLY	
MODEL	100340	FIRING PIN ASSEMBLY	
MODEL	1006		
MODEL	1006		
MODEL	1006		
DES. BY DATE	DRN. BY DATE	CHK. BY DATE	APP. BY DATE
	F. Martin	6-7-43	
TITLE			
ASSEMBLY			
NUMBER	SCALE	SUPERSEDES	REFERENCE
B-00340	2		
REMINGTON ARMS CO. INC.			
ILION RESEARCH DIV.			

B-100340 - 344