R2522567
BARBER - PRESALE R 0121579
CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

DO NOT SCALE THIS DRAWING WORK TO FIGURES

DRAWING NO. A-17044

THE REMINGTON ARMS CO. INC.
CENTRAL RESEARCH LABORATORY

SCALE: 4 X SIZE
ORDER NO.

TITLE: CLIP

MATERIAL: 2-1095 C.R. SPRING STEEL
H.T. SPEC. H.T.

DESIGNED BY	DATE	CHECKED BY	DATE	HARDNESS
M.W.	3-31-44	M.W.	3-14-46	72-75 RA

DRAWN BY	DATE	APPROVED	DATE	SURFACE TREATMENT
Hart	1-31-44	M.R.	6-26-46	TEMPER COLOR

	MODEL	PART NO.	PART USE	QTY.	BY	SEE
	21	17044	SAFETY SNAP WASH	1	M.W.	D-17036 X
	22	17044	" "	1	M.W.	D-17036 Y
	48X	17044	" "	1	M.W.	22565
(5)	40XCR	17044	" "	1	D.R.	21
	725	17044	SAFETY SNAP WASH	1	R.R.	D-22375
	725	17044	BOLT STOP PIN SNAP WASHER	1	R.R.	
(7)	760	17044	STOP LEVER PIN OR	1	R.R.	GP-220
(8)	760	17044	SAFETY SNAP WASH	1	R.R.	
(9)	760	17044	SAFETY SNAP WASH	1	R.R.	
	600	17044	" " "	1	R.J.	(12)
	600	17044	" "	1	R.R.	(13)
	40XR, 40XCR	17044	SAFETY SNAP WASH & OE TRIGGER	1	R.J.S.	
(4)	740	17044	SAFETY SNAP W	1	DD	RL

UNLESS OTHERWISE NOTED, TOLERANCES ON DECIMAL DIMENSIONS ARE ±.005 & ON FRACTIONAL DIMENSIONS ± 1/64

REFERENCE A 736 X

(2) FINISHES ARE DESIGNATED BY ROOT MEAN SQUARE (R. M. S.) MICRO-INCH ROUGHNESS VALUES AND ARE THE MAXIMUM ROUGHNESS ACCEPTABLE. UNLESS OTHERWISE SPECIFIED FINISH ROUGHNESS TO BE OR BETTER.

ALTERATIONS

LET.	WAS		BY	DATE
1	ADDED		R.A.	3-14-46
2	ADDED FINISH	SEE 3-77	R.R.	5-3-46
3	ADDED	DER 437	M.W.	3/8/53
4	ADDED	DER 2274	R.R.	3-14-56
5	ADDED		R.R.	7-28-57
6	REMOVED	SEE 3079	R.R.	2-13-58
7	FOR USE	SEE 3988	R.B.	10-30-58
8	ADDED	3941	R.R.	7-15-60
9	" 700A MODEL	4217	"	6-12-61
10	ADD USE	4431	R.R.	1/12/62
11	700A TO ADD	4445	R.R.	1/22/62
12	ADDED XB-12	4499	R.J.	5/1/62
13	ADD USE	5139	R.R.	1/22/63
14	ADD USE	6479	DD	3-14-66



RECOMMENDED ... TOLERANCE
MATERIAL
HEAT TREATMENT
HARDNESS
HEAT TREATMENT COLOR FINISH

SUPERSEDED
SEE REQ'S DATED 19 APR 66
ECN 6565

BARBER - PRESALE R 0121579