BARBER - PRESALE R 0121700

B-17017

THIS DRAWING OR INFORMATION IS PROPRIETARY INFORMATION TO THE REMINGTON ARMS COMPANY, INC.

DO NOT SCALE THIS DRAWING: WORK TO FIGURES UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:
1 PLACE (.1) - TOLERANCE ± .015
2 PLACE (.00) - TOLERANCE ± .010
3 PLACE (.001) - TOLERANCE ± .005
& ON FRACTIONAL DIMENSIONS ± 1/64
& ON ANGULAR DIMENSIONS ± 00°-30'
FINISHES ARE DESIGNATED BY ROOT MEAN SQUARE (R.M.S.) MICRO-INCH ROUGHNESS VALUES AND ARE THE MAXIMUM ROUGHNESS ACCEPTABLE. UNLESS OTHERWISE SPECIFIED.
FINISH ROUGHNESS TO BE 125 OR BETTER.

RECOMMENDED MATERIAL AND HEAT TREAT
MATERIAL C-1095 DRILL ROD
HEAT TREAT NITRIDING DRAW
HARDNESS RC 50-55
COLOR NONE
HEAT TREAT AND COLOR TO BE DONE BY REMINGTON

| ALTERATIONS | | | | |
|---|---|---|---|---|
| ALT. | WAS | REV. | BY | DATE |
| 52 | REDRAWN WAS A-17017 | | W.P. | 1-29-86 |

FOR BLANK DRAWING
SEE A-13974




NOTE: MAX.ECCENTRICITY FOR
.075/.070 DIA. .1406/.1400 DIA.
TO BE .003 (.006 T.I.R.)

| MODEL | PART NO. | PART USE |
|---|---|---|
| NBAR | 17017 | EJECTOR |
| 7LWT | 17017 | EJECTOR |
| XP-100 | 17017 | EJECTOR |
| 40XCF | 17017 | EJECTOR |
| 700 | 17017 | EJECTOR |

| DES. BY DATE | DR. BY DATE | CHK. BY DATE | APP. BY DATE |
|---|---|---|---|
| | W.P. 1-29-86 | FEM 12-3-86 | DBF 6-18-86 |

TITLE EJECTOR

| NUMBER | SCALE | SUPERSEDES | REFERENCE |
|---|---|---|---|
| B-17017 | 2X | | |

REMINGTON ARMS CO. INC.
ELION RESEARCH DIV.

CV FILENAME - RES.SMM.NBAR.EJECTOR

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON
BARBER - PRESALE R 0121700
R2522688