

4.5° CHAMFER

RECOMMENDED MATERIAL AND HEAT TREAT

MATERIAL 9151-52100
 HEAT TREAT
 HARDNESS R45N 93-98
 COLOR BLACK OXIDE
 HAZARD

B-17022

21
 22
 26 15

700BDL	FIRING PIN CROSS PIN	C2G335
700ADL	FIRING PIN CROSS PIN	P.L.
40XCF	FIRING PIN CROSS PIN	P.L.
413	FIRING PIN CROSS PIN	P.L.
412A	FIRING PIN CROSS PIN	P.L.
412	FIRING PIN CROSS PIN	P.L.
725	FIRING PIN CROSS PIN	P.L.
411-C	FIRING PIN CROSS PIN	P.L.
411-B	FIRING PIN CROSS PIN	22555
40-X	FIRING PIN CROSS PIN	22555
722	FIRING PIN CROSS PIN	Y22040
721	FIRING PIN CROSS PIN	Y22040
MODEL	PART USE	QUAN. SEC.
DES'D BY DATE	DRAWN BY DATE	CHECK BY DATE
	G. REED 5-16-62	4 6-11-62
APPR. BY DATE		
VLS 12/62		
TITLE		
PIN		
NUMBER	SCALE	SUPPLEMENTARY REFERENCE
B-17022	5:1	A-17022
REMINGTON ARMS CO. INC.		
RESEARCH & DEV. DEPT.		