

R2522709
BARBER - PRESALE R 0121721

Obsec-E		THIS DRAWING OR INFORMATION IS PROPRIETARY INFORMATION TO THE REMINGTON ARMS COMPANY, INC.		DO NOT SCALE THIS DRAWING. WORK IN PENCIL. UNLESS SPECIFIED OTHERWISE, DIMENSIONS ARE GIVEN IN DECIMAL INCHES UNLESS NOTED OTHERWISE. DIMENSIONS OF FRACTIONS SHALL BE AS SHOWN. ALL DIMENSIONS SHOWN ON THIS DRAWING ARE UNLESS OTHERWISE SPECIFIED IN MILLIMETERS AND ARE FOR THE MAXIMUM DIMENSION. HOLE LOCATIONS SHALL BE SPECIFIED BY CENTER POINTS. FINISH DIMENSIONS TO BE SPECIFIED BY FINISH.		COMMENCED MATERIAL AND HEAT TREAT		ALTERATIONS			
REV.	DATE	BY	CHKD.	APP.	DATE	REASON	MATERIAL	HEAT TREAT	HARDNESS	COLOR	HEAT TREAT AND COLOR TO BE DONE BY REMINGTON
3						Revised & Redrawn					
4						ADD USED (TWO VAR LONG)					
5						ADDED 700 ADL-1983 222, 243, 300, 6 mm, 22-250.					
6						ADDED 700 ADL-1983 222, 243, 250, 6 mm, 22-250.					

ASSEMBLY INCLUDES:

PART NO	BOLT PLUG	FIRING PIN	F. PIN CROSS PIN	F. PIN HEAD	MAIN SPRING
22040	17012	22020	17022	23320	17029
22041	17012	22021	17022	23320	17058
22042	92510	22021	"	"	"
22043	"	22020	"	"	17029

NOTE:
700 "LONG" ACTION INCLUDES:
264, 7mm, 300 WIN MAG, 270, 30-06, 25-06 CAL.

REV.	DATE	BY	CHKD.	APP.	DATE	REASON
6						700 "83 ADL 22043 FIRING PIN ASSEM - 270, 30-06, 25-06, 7mm REM MAG.
5						700 "83 ADL 22042 FIRING PIN ASSEM - 222, 243, 300, 6 mm, 22-250.
4						700 "83 CF 22041 FIRING PIN ASSEM. B-2635
3						700 VARM 22041 " " " "
2						700 SHORT 22041 " " " "
1						700 LONG 22040 " " " "

ASSEMBLY

B-22040 3/19/68
REMINGTON ARMS CO. INC.