

RECOMMENDED MATERIAL AND HEAT TREAT
MATERIAL PM HD 1000
HEAT TREAT
HARDNESS
COLOR
HEAT TREAT AND COLOR TO BE DONE BY
REDMONTON P.B.J. 11/1/60

ALTERATIONS

ALT.	WAS	BY	DATE
1	ADD USE 7207	11/17/60	11/17/60
2	180/126	11/17/60	11/17/60

DO NOT SCALE THIS DRAWING. WORK TO DIMENSIONS UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:
 1 PLACE (1) - TOLERANCE ± .010
 2 PLACE (2) - TOLERANCE ± .005
 3 PLACE (3) - TOLERANCE ± .001
 4 PLACE (4) - TOLERANCE ± .0005
 5 PLACE (5) - TOLERANCE ± .0002
 6 PLACE (6) - TOLERANCE ± .0001
 7 PLACE (7) - TOLERANCE ± .00005
 8 PLACE (8) - TOLERANCE ± .00002
 9 PLACE (9) - TOLERANCE ± .00001
 10 PLACE (10) - TOLERANCE ± .000005
 11 PLACE (11) - TOLERANCE ± .000002
 12 PLACE (12) - TOLERANCE ± .000001
 DIMENSIONS ARE EXPRESSED IN INCHES UNLESS OTHERWISE SPECIFIED.
 DIMENSIONS ARE EXPRESSED IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
 DIMENSIONS ARE EXPRESSED IN INCHES UNLESS OTHERWISE SPECIFIED.
 DIMENSIONS ARE EXPRESSED IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.

NOTE:
RESIN IMPREGNATE

**FOR FINISH DRAWING
 SEE B-14651**

1

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86