

.003 MAX. BOW
ALLOWED IN THIS
DIRECTION ONLY.

BARBER - PRESALE R 0121866

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

TENSION SHOWN

NOTE

1. CHECK MATERIAL THICKNESS AFTER BENDING BY LOCATING ON BODY WITH LONG LEG RESTING ON SURFACE AT 90° CHECK FROM 90° SURFACE TO TOP SURFACE OF LONG LEG
2. INSIDE SURFACE MUST BE SMOOTH, CLEAN, AND FREE OF BURRS.
3. PART MUST NOT PUCK WHEN INSIDE SURFACE REST ON A FLAT SURFACE MAX. BEND TWIST OR BOW ALLOWED IS .003

MEN 600		TRIGGER CONNECTOR	
MODEL	PART NO.	PART USE	
DES. BY DATE	CHK. BY DATE	CHK. BY DATE	APP. BY DATE
	E. MARTIN 22 NOV. 77	11-22-77	12/1/77
TITLE CONNECTOR			
NUMBER	SCALE	SUPP. BY DATE	REFERENCE
C-15436	4X	A-15436 FEB. 5	REMINGTON ARMS CO. INC. ILION RESEARCH DIV.

BARBER - PRESALE R 0121866 R2522854