BARBER - PRESALE R 0121879




LEAD CORNERS AT REAR
GS TO PREVENT HARD
RECEIVER.

| | | | | |
|---|---|---|---|---|
| 22 | REMOVE 3° TAPER | 5986 | B6 | 12/1/65 |
| 23 | REDIM. .985 TO 1.059 | " | " | " |
| 24 | ADDED IN 600 6.5mm Rem. Mag. | 6075 | J | 1/6/65 |
| 25 | 1.059 | 6128 | " | 5/25/65 |
| 26 | .015 R Max. | 6669 | F | 10/14/66 |
| 27 | ADD USE 660 MAG. | 6669 | NF | 8/16/66 |
| 28 | ADD USE 700 BOLT 6.5 x .30 | 7630 | [illegible] | [illegible] |
| 29 | ADDED USE | 8958 | [illegible] | [illegible] |

| | | |
|---|---|---|
| 27 | MENAUK BOLT | BOLT HEAD - 6.5 x 350 MAG |
| 28 | 700 BOLT | BOLT HEAD 6.5 x 350 MAG |
| 27 | 660 | BOLT HEAD 6.5 x 350 MAG |
| 24 | 600 | BOLT HEAD 6.5mm Rem. Mag. |
| 21 20 | 600 | BOLT HEAD 350 REM MAG |
| 17 | 700 B.C. | BOLT HEAD - 300 H&H |
| | 700 ADL BOLT | BOLT HEAD - 7mm REM. MAG |
| | 700 DOU BOLT | [illegible] |
| | 720 B.C. | BOLT HEAD - .458 WIN. |
| | 700 B.C. | [illegible] |
| MODEL | PART USE | |

| | | | |
|---|---|---|---|
| DESIGNED BY DATE | DRAWN BY DATE 6-25-65 | CHECKED BY DATE | [illegible] |
| TITLE BOLT HEAD | | | |
| NUMBER 6-15-810 | | SCALE | REPLACES [illegible] |
| REMINGTON ARMS CO. INC. BRIDGEPORT, CONN. | | | |

| | | |
|---|---|---|
| NUMBER | BOLT HEAD - 8mm Rem. Mag. | 6-25-65 |
| MODEL | PART USE | SCALE |

BARBER - PRESALE R 0121879

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

R2522867