C-102515

THIS DRAWING OR INFORMATION IS PROPRIETARY INFORMATION TO THE REMINGTON ARMS COMPANY, INC.

DO NOT SCALE THIS DRAWING; REFER TO FIGURES UNLESS OTHERWISE NOTED.
TOLERANCES ON DECIMAL DIMENSIONS ARE:
1 PLACE .X - TOLERANCE ± .010
2 PLACE .XX - TOLERANCE ± .005
3 PLACE .XXX - TOLERANCE ± .002
4 OR FRACTIONAL DIMENSIONS ± .001
ANGULAR DIMENSIONS ± 30'
FIGURES ARE DESIGNATED BY BODY HEAD SHAPE (E.G.) VERO-HIGH HARDNESS VALUES ARE FOR THE HARDNESS ACCEPTABLE. UNLESS OTHERWISE SPECIFIED.
FINISH DIMENSIONS TO BE ✓ OR BETTER.

RECOMMENDED MATERIAL AND HEAT TREAT
MATERIAL
HEAT TREAT
HARDNESS
COLOR
HEAT TREAT AND COLOR TO BE DONE BY REMINGTON

ALTERATIONS				
ALT.		REF.	BY	DATE



FIRING PIN ASS Y	FIRING PIN CROSS PIN	BOLT PLUG WASHER	FIRING PIN	FIRING PIN HEAD	MAINSPRING
102515	93679	93633	102520	93699	17029
102516	93679	93633	102521	93699	17058

NBAR	102516	FIRING PIN ASS'Y-SHORT ACTION
NBAR	102515	FIRING PIN ASS'Y-LONG ACTION
USED ON	PART NO.	PART USE

DES. BY DATE: | DWN. BY DATE: LRS 8-22-85 | CHK. BY DATE: FEW 3-13-86 | APP. BY DATE:

TITLE FIRING-PIN-ASSY-LONG ACTION

C-102515 | SCALE 2X | REMINGTON ARMS CO. INC.

CV FILENAME - REM.DWG.NBAR.FIRING-PIN-ASSY-LA