

BARBER - R 0000071

THIS DRAWING OR INFORMATION IS  
PROPRIETARY INFORMATION TO THE  
REMINGTON ARMS COMPANY, INC.

DO NOT SCALE THIS DRAWING: WORK TO FIGURES  
UNLESS OTHERWISE NOTED.  
TOLERANCES ON DECIMAL DIMENSIONS ARE:  
1 PLACE (0.1) - TOLERANCE  $\pm 0.015$   
2 PLACE (0.01) - TOLERANCE  $\pm 0.010$   
3 PLACE (0.001) - TOLERANCE  $\pm 0.005$   
& ON FRACTIONAL DIMENSIONS  $\pm 1/64$   
& ON ANGULAR DIMENSIONS  $\pm 0.5^\circ$   
FINISHES ARE DESIGNATED BY ROOT MEAN  
SQUARE (R.M.S.) MICRO-INCH ROUGHNESS  
VALUES AND ARE THE MAXIMUM ROUGHNESS  
ACCEPTABLE, UNLESS OTHERWISE SPECIFIED.

FINISH ROUGHNESS TO BE  
DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE  
WITH ASME Y14.5-1994.

### MATERIAL AND HEAT TREAT

MATERIAL: ASME B18.3 STAINLESS

HEAT TREAT: VENDOR'S SPEC

HARDNESS: HRB 80-100


FINISH: NONE

~~HEAT TREAT AND FINISH TO BE DONE BY REMINGTON~~


### ALTERATIONS

| ALT. | ZONE   | WAS                      | REF. | BY  | DATE     |
|------|--------|--------------------------|------|-----|----------|
| A    | E1, E2 | CORRECTED THREAD IN VIEW |      | JWR | 10-17-06 |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |
|      |        |                          |      |     |          |


A



1/16" HEX KEY SOCKET  
SEE NOTE 2



SEE NOTE 1



#5-40 UNC-2A

A

.080 MIN.  
SEE NOTE 2

.010 X 45° MAX

.045

R=1/2W

.025

### NOTES:

1. NYLON LOCKING ELEMENT OR ENGINEERING APPROVED EQUIVALENT  
REQUIRED ON THREADS AS INDICATED.
2. HEX KEY SOCKET TO CONFORM TO ASME B18.3-1998.

SolidWorks Filename: 301429 - Trigger Pull Adjustment Screw

NOT RELEASED FOR PRODUCTION

|                                               |                             |              |
|-----------------------------------------------|-----------------------------|--------------|
| MODEL                                         | PART NO.                    | PART USE     |
| DES. BY DATE<br>JWR 8-30-06                   | DRN. BY DATE<br>JWR 8-31-06 | CHK. BY DATE |
| TITLE<br>TRIGGER PULL ADJUSTMENT SCREW        |                             |              |
| SHEET SIZE<br>B                               | NUMBER<br>301429            | SCALE<br>10X |
| SUPERSEDES                                    |                             | REFERENCE    |
| REMINGTON ARMS CO., INC.<br>Madison, NC 27025 |                             |              |