

- ISS (Integrated Security System), J key operated

30 ISS/J-KEY

31 BARREL/ACTION

- Drilled and tapped for scope mounts
- Uniform scope mounting surfaces
- 3 RINGS OF STEEL
- 3 LOCKING LUGS THAT LOCK INTO BARREL
- 60 degree bolt throw
- Bolt liner is nylon, reinforced fiberglass with Teflon and silicon additives
- All steel bolt handle, swept rearward and downward with knurling
- Bolt field strippable without tools
- ISS (Integrated Security System), J key operated
- External bolt release lever

32 BARREL/ACTION

- Drilled and tapped for scope mounts
- Uniform scope mounting surfaces
- 3 RINGS OF STEEL
- 3 LOCKING LUGS THAT LOCK INTO BARREL
- 60 degree bolt throw
- Bolt liner is nylon, reinforced fiberglass with Teflon and silicon additives
- All steel bolt handle, swept rearward and downward with knurling
- Bolt field strippable without tools
- ISS (Integrated Security System), J key operated
- External bolt release lever
- Bolt operates with safety switch in any position (no bolt lock)

33 BARREL/ACTION

- Drilled and tapped for scope mounts
- Uniform scope mounting surfaces
- 3 RINGS OF STEEL
- 3 LOCKING LUGS THAT LOCK INTO BARREL
- 60 degree bolt throw
- Bolt liner is nylon, reinforced fiberglass with Teflon and silicon additives
- All steel bolt handle, swept rearward and downward with knurling
- Bolt field strippable without tools
- ISS (Integrated Security System), J key operated
- External bolt release lever
- Bolt operates with safety switch in any position (no bolt lock)
- Factory set trigger at 3.5 - 5 pounds

34 BARREL/ACTION

- Drilled and tapped for scope mounts
- Uniform scope mounting surfaces
- 3 RINGS OF STEEL
- 3 LOCKING LUGS THAT LOCK INTO BARREL
- 60 degree bolt throw
- Bolt liner is nylon, reinforced fiberglass with Teflon and silicon additives
- All steel bolt handle, swept rearward and downward with knurling
- Bolt field strippable without tools
- ISS (Integrated Security System), J key operated
- External bolt release lever
- Bolt operates with safety switch in any position (no bolt lock)
- Factory set trigger at 3.5 - 5 pounds
- Trigger set to 14700

35 TRIGGER VIEW

36 BARREL/ACTION

- Drilled and tapped for scope mounts
- Uniform scope mounting surfaces