

**FBI Sniper Rifle Proposal
"Model 40-X S.W.A.T. Deployment Rifle"**

Three Complete Samples to FBI by 7/21/03

Product Specifications

- Model 40-X stainless steel right hand short action with M-24 Powder Coat Finish
 - Serial Number to contain "FBI" suffix
 - Receiver rolled as Remington Model 40-X
 - Bolt will have M-24 Sandstrom Finish
 - Bolt handle will be roll pinned to bolt body
 - Bolt plug will be powder coated to match receiver
 - Scope mounting holes will be over sized to 8-40 same as M-24
 - Magazine box, follower & spring will have M-24 Sandstrom Finish
- Stainless steel 24" Model 40-X button rifled barrel with M-24 Powder Coat Finish
 - Chambered for .308 Win (SAAMI Specifications)
 - Twist rate 1:10 (SAAMI Specifications) 6-Groove Button Rifled
 - Twist rate and caliber rolled on barrel
 - Standard 40-X barrel contour
 - Protective crown
 - Barrell free-floating
 - Headspace not to exceed 1.633"
 - Accuracy specification stated as ½ MOA 5-shot group out of box, 1 MOA after 5k rounds
- Model 700 stainless steel fire control
 - Trigger pull set at 3.75 lbs
- Trigger floorplate assembly will be Sunny Hill all steel model
- H.S. Precision Pro-Series 2000 Tactical Stock w/ aluminum bedding block
 - Adjustable comb
 - Add witness mark to comb and witness marks on stock for adjustment reference points
 - Adjustable length of pull
 - Add witness marks on either top or bottom butt pad posts to serve as adjustment reference points
 - Limbsaver/R3 recoil pad will be added in place of standard butt plate
 - Stock and magazine configuration must be configured to hold 5-rounds in the magazine (6-round total capacity for firearm)
 - Must be equipped with standard LE three swivel stud configuration
 - Color will be standard M-24 black
 - Action will be positively bedded to aluminum bedding block
- Leupold Vari-X III 3.5-10x40 Long Range M1 scope with Mil-Dot reticle and 30mm tube
 - Equipped with Butler Creek Flip-up lens covers (supplied with scope from Leupold)