

rounds
There are damaged, broken or mis-aligned components

Some rifles are missing components

<table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 100%; background-color: #C8C8BF; height: 28px; vertical-align: top;"> 7.62 mm M24 SNIPER WEAPONS SYSTEM (SWS) </td> </tr> <tr> <td style="width: 100%; background-color: #E7E7E7; height: 94px; vertical-align: top;"> Action </td> </tr> <tr> <td style="width: 100%; background-color: #E7E7E7; height: 94px; vertical-align: top;"> Remington Model 700 production long action receiver </td> </tr> <tr> <td style="width: 100%; background-color: #E7E7E7; height: 94px; vertical-align: top;"> with M/40X custom trigger Bolt handle knob is smooth. Fire control is externally adjustable from two to eight pounds pull. </td> </tr> <tr> <td style="width: 100%; background-color: #E7E7E7; height: 94px; vertical-align: top;"> Accuracy exceeds the U.S. Government requirement for a sniper weapon that would retain its zero under adverse conditions (including airborne operations) and be capable of attaining 1.3 inches Average Mean Radius (A.M.R.) at 200 yards. </td> </tr> <tr> <td style="width: 100%; background-color: #FFFFFF; height: 60px; vertical-align: top;"> Barrel </td> </tr> <tr> <td style="width: 100%; background-color: #FFFFFF; height: 60px; vertical-align: top;"> Round, 24" free-floating, 416-R stainless steel barrels were initially manufactured by the Rock Barrel Company. Remington now makes the barrels in-house. The bore is especially rifled for the M118 special ball cartridge. Remington 5-R rifling has an unconventional five lands and grooves. The twist is 1 turn in 11.25-inches. </td> </tr> </table>	7.62 mm M24 SNIPER WEAPONS SYSTEM (SWS)	Action	Remington Model 700 production long action receiver	with M/40X custom trigger Bolt handle knob is smooth. Fire control is externally adjustable from two to eight pounds pull.	Accuracy exceeds the U.S. Government requirement for a sniper weapon that would retain its zero under adverse conditions (including airborne operations) and be capable of attaining 1.3 inches Average Mean Radius (A.M.R.) at 200 yards.	Barrel	Round, 24" free-floating, 416-R stainless steel barrels were initially manufactured by the Rock Barrel Company. Remington now makes the barrels in-house. The bore is especially rifled for the M118 special ball cartridge. Remington 5-R rifling has an unconventional five lands and grooves. The twist is 1 turn in 11.25-inches.
7.62 mm M24 SNIPER WEAPONS SYSTEM (SWS)							
Action							
Remington Model 700 production long action receiver							
with M/40X custom trigger Bolt handle knob is smooth. Fire control is externally adjustable from two to eight pounds pull.							
Accuracy exceeds the U.S. Government requirement for a sniper weapon that would retain its zero under adverse conditions (including airborne operations) and be capable of attaining 1.3 inches Average Mean Radius (A.M.R.) at 200 yards.							
Barrel							
Round, 24" free-floating, 416-R stainless steel barrels were initially manufactured by the Rock Barrel Company. Remington now makes the barrels in-house. The bore is especially rifled for the M118 special ball cartridge. Remington 5-R rifling has an unconventional five lands and grooves. The twist is 1 turn in 11.25-inches.							