

holes for receiver sight. Steel trigger guard and floor plate are manufactured by Dakota Arms.

</font></td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#EFEFE7" height="24">

<b><font face="Verdana" size="1">Receiver marking:</font></b></td>

<td width="79%" valign="top" bgcolor="#EFEFE7" height="24">

<font face="Verdana" size="1">Remington M700 / M24 and U.S. is stamped on rifles intended for the U.S. Army.</font></td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#FFFFFF" height="24">

<b><font face="Verdana" size="1">Safety:</font></b></td>

<td width="79%" valign="top" bgcolor="#FFFFFF" height="24">

<font face="Verdana" size="1">Ambidextrous two-position safety modified to give equal on/off safety force</font></td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#EFEFE7" height="48">

<b><font face="Verdana" size="1">Scope:</font></b></td>

<td width="79%" valign="top" bgcolor="#EFEFE7" height="48">

<font face="Verdana" size="1">Leupold-Stevens Ultra M-3A day optic sight, fixed at 10-power, with Mil Dot system range-finding reticle &nbsp; Has a bullet drop compensator and is adjustable for parallax (focus). The scope caps are commercially available from Butler.</font></td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#FFFFFF" height="24">

<b><font face="Verdana" size="1">Serial number location:</font></b></td>

<td width="79%" valign="top" bgcolor="#FFFFFF" height="24">

<font face="Verdana" size="1">Bottom of turret (same as product B.A.C.F.).</font></td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#EFEFE7" height="24">

<b><font face="Verdana" size="1">Serial number range:</font></b></td>

<td width="79%" valign="top" bgcolor="#EFEFE7" height="24">

<font face="Verdana" size="1">Concurrent with Model 700 production.</font></td>

</tr>

<tr>

<td width="21%" valign="top" bgcolor="#FFFFFF" height="108">

<b><font face="Verdana" size="1">Stock:</font></b></td>

<td width="79%" valign="top" bgcolor="#FFFFFF" height="108">

<font face="Verdana" size="1">One-piece Synthetic Kevlar and graphite composite stock manufactured by H-S Precision, (from a pattern submitted by Remington) with an aluminum bedding block throughout. Adjustable length of pull (12 to 14