Ron,

As requested we have reviewed this program with Diaz's group and Mayfield and have put together a test plan to qualify this product for production. The short action utilizes the same parts as the existing M/710 with the following exceptions:

## PART DIFFERENCES

- Magazine Box
- \* Magazine Follower
- \* Magazine Box Bottom
- \* Receiver Insert
- Support Bracket
- \* SPL Fire Control
- \* Magazine Box Spacer

Changes to the stock tool will be required to add additional clearance for the safety arm/button and the fire control housing. The receiver rear diameter that accepts the new insert will also be different (larger) than the existing M/710.

With these changes the main focus in testing will be accuracy (for the 3 new calibers), feeding, and then function, endurance and abuse testing due to the integration of a new fire control in the Model 710 action. Based on manufacturing methods to produce parts, the long tooling lead times, and the risk involved a combined DAT/T&P test was requested. I concur with this approach. Since this will also be a T&P class test we should still sample product from a larger pool. With three calibers Mayfield's plan to build 50 guns/caliber should be adequate. We will randomly select 10 guns of each caliber for our test for a total sample size of 30 guns. With that said the following tests are planned:

## TEST & MEASUREMENTS

- Out of Box Inspection (All 30 Guns)
  - (Packaging, cosmetics, etc.)
- Preliminary Measurements & Tests (All 30 Guns)
  - \* Headspace/Proof/Headspace
  - \* Check Chamber Dimensions, Bore, Groove, Twist Rate
  - \* Check Bolt Head and Barrel Hardness
  - \* Firing Pin Indent
  - \* Trigger Rull + other SPL Specific Measurements (Engagement, Over Travel, etc.)
  - ' Slam Test -- 3 Guns
- Jack Function (All 30 Guns)
  - \* 200 rds./Gun using Rem. and Competitive Ammo Types
- \* Accuracy (5 Guns/Caliber)

Subject to Protective Order - Williams v. Remington