

Page 2

BARREL-- All features of the barrel used in this rifle meet or exceed the specifications called for in this solicitation.

- Stainless steel 24" Model 40-X button rifled barrel with non-reflective polymer based finish
- Chambered for .308 Win (SAAMI Specifications)
- Twist rate 1:10 (SAAMI Specifications) 6-Groove Button Rifled
- Twist rate and caliber rolled on barrel
- Standard 40-X barrel contour (similar to Douglas #6 contour)
- Protective crown
- Barrel free-floating
- Headspace 1.630" Min. to 1.633" Max.
- Accuracy specification stated as 1/4 MOA 5-shot group out of box, 1 MOA after 5k rounds

TRIGGER

- Model 700 stainless steel fire control
- Trigger pull set at 3.75 lbs
- Entire trigger assembly is weather impervious
- Trigger is adjustable only by factory or authorized gunsmith

TRIGGER FLOORPLATE ASSEMBLY

- Trigger floor plate assembly is the Sunny Hill all steel model
- Allows for 5 shot magazine capacity, 6 round total capacity
- Trigger floor plate assembly is coated with non-reflective polymer based finish

STOCK

- H.S. Precision Pro-Series 2000 Tactical Stock w/ aluminum bedding block
- Adjustable comb
 - Witness marks on stock to serve as adjustment reference points
- Adjustable length of pull
 - Witness marks on stock to serve as adjustment reference points
- 1" rubber recoil pad
- Equipped with standard LE three swivel stud configuration – stud epoxied in place
- Stock color is charcoal gray

SCOPE, MOUNT AND RINGS

- Leupold Vari-X III 3.5-10x40 Long Range M1 scope with Mil-Dot reticle and 30mm tube
- Equipped with Butler Creek Flip-up lens covers (supplied with scope from Leupold)