Page 3

- · Scope lenses are fully multi-coated
- Scope windage and elevation dials are target style and have '4" MOA click adjustments
- Windage and elevation dials are resettable to zero after sighting in the rifle
- Zero mark is lockable
- Scope finish is black non-reflective
- Scope is fully waterproof
- Picitinny style scope rail will be from Badger Ordnance Company
- Scope Rings will be from Badger Ordnance Company
- Scope has been mounted and zeroed at 100 vds. prior to shipment

BI-POD (with Pod Lock)

- Rifle utilize a Harris LMS Bi-pod
- To include Pod Loc &

SLING

Rifle will be packed with black synthetic Turner AWS Sling

PHYSICAL DIMENSIONS

- Rifle Overall Length 43.5
- Deployment Weight 14.5 lbs
 - Rifle Width 2

TOOLS

- Rifle will include tool kit consisting of:
- Torque wrench preset to factory settings with rifle serial number marked on wrench
- Hex wrench to disassemble action from stock with rifle serial number marked on tool
- Kleinendorst style bolt disassembly tool with rifle serial number marked on tool

SYSTEM CASE

- The entire system is packed in a lockable Pelican 1750 style deployment case.
 - Case equipped with atmospheric purge valve
 - Case equipped with integral wheels for travel
 - Case is waterproof, airtight, crush resistant and dust-proof
 - Case will store the complete rifle system and all of its components excluding ammunition, cleaning solvents and replacement parts.