

accidental firing

Discussion Thread

Response (Chris)  
Dear Mr. Salekin,

6/8/2004 11:56:45 AM

We prefer to inspect the rifle with an incident as you described. The trigger may need a good cleaning. We offer a product called RemAction Cleaner that can be sprayed into the trigger assembly to clean out the old lubricants and debris. You would spray it in various areas of the trigger until the liquid runs out clear. It is a self-drying cleaner. You should apply Remoil as described in your owner's manual.

If you will complete the form located through the link below we will forward to you a copy of the original owner's manual.

<http://www.remington.com/whatsnew/readroom.htm>

You can also find owner's manuals for some of our current models on-line in our Reading Room in the "What's New" Section.

Your rifle was originally installed with a bolt lock, which means you have to put the safety switch on fire before you can open the bolt. We are offering a conversion at a special price if you would like your firearm converted, so that you can open the bolt at anytime with the safety on safe. To view more details regarding this modification, go to:

[http://www.remington.com/Safety\\_Modification\\_Program/remington\\_safety.htm](http://www.remington.com/Safety_Modification_Program/remington_safety.htm)

We can remove the bolt lock and inspect at a Remington Authorized Repair Center. To find your closest center, go to:

<http://www.remington.com/repairsvc/modelselection.asp>

Customer (Charles Salekin)

6/5/2004 1:33:28 PM

> Request suggestion, tip, "try this" or whatever- Thnx!

>