

The Operating Handle

The operating handle is used to pull the bolt rearward to open the action. See Picture 7.

WARNING: When the operating handle is forward as shown in Picture 7, the bolt is closed and the firearm can be fired.

The Carrier Release

1. Point the firearm in a safe direction.
2. Engage the safety mechanism. **RED BAND WILL NOT SHOW.**
3. **CAUTION:** Keep your fingers away from the ejection port and operating handle.
4. Push the carrier release to close the action. See Picture 8.

The Trigger

Putting the trigger fires the firearm.

The weight of the trigger pull is preset at the factory.

All adjustments to the trigger and trigger plate assembly must be made by the factory or a REMINGTON® AUTHORIZED GUNSMITH.

WARNING: NEVER put your finger on the trigger unless you are going to fire the firearm.

The Barrel

The inside of the barrel must be clean and free of obstructions.

I. TO CHECK THE INSIDE OF THE BARREL:

WARNING: LOOK INTO THE SIGHT ON PORT CHECK THE CHAMBER AND MAGAZINE TO MAKE SURE THERE ARE NO SHOT CHIPS IN THE AREA.

1. Point the firearm in a safe direction.
2. Engage the safety mechanism. Make sure the **RED BAND IS NOT SHOWING.**
3. Pull the operating handle fully rearward until the bolt is locked open.
4. Insert a cleaning rod into the muzzle. Push the rod completely through the barrel until rod can be seen in the ejection port.

WARNING: MODEL 11-87T BARRELS CAN NOT BE USED IN REPLACEMENT BARRELS ON MODEL 11-87T FIREARMS. MODEL 11-87T BARRELS CAN NOT BE USED IN REPLACEMENT BARRELS ON MODEL 11-87T FIREARMS.

MODEL 11-87 SUPER MAGNUM® BARREL REPLACEMENT

ONLY MODEL 11-87 12 GA. RIF. BARRELS -AVING THE CHAMBER AND SIGHT ON PORT ON MODEL 11-87 SUPER MAGNUM FIREARMS.

REPLACE WITH GASTON MFG. (ANTHONY) BARREL EXT. MODEL 11-87 AND 11-87T IN THE JERSEY II "TRANS" TO A RELIEVED MARKED MODEL 11-87 SUPER MAGNUM.

WARNING FOR MODEL 11-87 LIGHT CONTOUR 12 GAUGE BARRELS

WARNING: DO NOT overclean or follow any barrel of your MODEL 11-87 LIGHT CONTOUR Barrel shotgun. The weight reduction in this barrel is achieved by making the barrel lighter to the minimum SAFE dimension. Any additional reduction in this barrel with "CLEAN" and "CLEAN" barrel cleaning will lead to a barrel failure and result in serious personal injury.

II. TO REMOVE OBJECT FROM INSIDE THE BARREL:

WARNING: NEVER try to remove an object from the barrel by loading, ejecting, and firing. This may cause the barrel to burst or a catastrophic failure and cause serious personal injury.

1. Remove the barrel following the procedure shown on pages 14 and 15.
2. Use the correct cleaning rod.
3. Insert cleaning rod into the muzzle and lightly tap rod to free object(s).
4. If an object cannot be easily pushed out of the barrel with a cleaning rod, return the firearm to the factory or a REMINGTON AUTHORIZED GUNSMITH.