

John Trull

From: Trull, John
 Sent: 07/02/2003 06:11:44 PM
 To: Foster, Greg
 CC:
 BCC:
 Subject: FBI Rifle Solicitation

As we discussed.....

FBI Sniper Rifle Proposal
 "Model 40-X S.W.A.T. Deployment Rifle"

Three Complete Samples to FBI by 7/21/03

Product Specifications

- * Model 40-X stainless steel right hand short action with M-24 Powder Coat Finish
- * Serial Number to contain "FBI" suffix
- * Receiver rolled as Remington Model 40-X
- * Bolt will have M-24 Sandstrom Finish
- * Bolt handle will be roll pinned to bolt body
- * Bolt plug will be powder coated to match receiver
- * Scope mounting holes will be over sized to 3-40 same as M-24
- * Magazine box, follower & spring will have M-24 Sandstrom Finish
- * Stainless steel 24" Model 40-X button rifled barrel with M-24 Powder Coat Finish
- * Chambered for .308 Win (SAAMI Specifications)
- * Twist rate 1:10 (SAAMI Specifications) 6-Groove Button Rifled
- * Twist rate and caliber rolled on barrel
- * Standard 40-X barrel contour
- * Protective crown
- * Barrell free-floating
- * Headspace not to exceed 1.633"
- * Accuracy specification stated as 1/2 MOA 5-shot group out of box, 1 MOA after 5k rounds
- * Model 700 stainless steel fire control
- * Trigger pull set at 3.75 lbs
- * Trigger floorplate assembly will be Sunny Hill all steel model
- * H.S. Precision Pro-Series 2000 Tactical Stock w/ aluminum bedding block
- * Adjustable comb
- * Add witness mark to comb and witness marks on stock for adjustment reference points
- * Adjustable length of pull
- * Add witness marks on either top or bottom butt pad posts to serve as adjustment reference points
- * Limbsaver/R3 recoil pad will be added in place of standard butt plate
- * Stock and magazine configuration must be configured to hold 5-rounds in the magazine (6-round total capacity for firearm)
- * Must be equipped with standard LE three swivel stud configuration
- * Color will be standard M-24 black
- * Action will be positively bedded to aluminum bedding block
- * Leupold Vari-X III 3.5-10x40 Long Range M1 scope with Mil-Dot reticle and 30mm tube
- * Equipped with Butler Creek Flip-up lens covers (supplied with scope from Leupold)
- * Scope rail will be Nightforce picatinny
- * Scope Rings will be Nightforce to match rail
- * Scope will be mounted and zeroed at 100 yds prior to shipment
- * Rifle will be packed with Harris LMS Bi-pod in case

Subject to Protective Order - Williams v. Remington