

HANDGUN DUTY AMMUNITION BALLISTICS

A Full Line of Superior "Street System" Tested Ammunition with Performance that Meets Today's Stringent Requirements.

Remington Handgun Duty Ammunition comes in a wide variety of calibers, bullet types, and loads to meet your requirements.

Remington Pistol and Revolver Duty Ammunition Ballistics

Caliber	Index ECP No.	Rimfire In.	Primer No.	Wt. Grs.	Bullet Style	Velocity (ft./sec.)			Energy (ft./lbs.)			Mid-Range Trajectory (in.)	
						Muzzle	25 yds.	50 yds.	Muzzle	25 yds.	50 yds.	25 yds.	50 yds.
2.56 (35mm) Auto	R25AP	22200	1 1/2	50	Metall Case	761	717	685	74	41	30	1.5	2.0
32 S&W	R32SW	22204	1 1/2	88	Lead	680	645	610	90	81	73	0.6	2.5
32 S&W Long	R32SWL	22208	1 1/2	98	Lead	705	670	635	119	98	88	0.6	2.3
32 (7.65mm) Auto	R32AP	22212	1 1/2	71	Metall Case	905	855	810	129	115	107	0.4	1.4
357 Mag**	R357M	22228	5/8	130	Semi-Jacketed Hollow Point	1285	1224	975	410	292	232	0.2	0.8
	R357M1	22216	5/8	125	Semi-Jacketed Hollow Point	1451	1440	1080	483	427	330	0.1	0.6
	R357M2	22213	5/8	130	Semi-Jacketed Hollow Point	1385	1304	1015	435	420	365	0.2	0.8
	R357M3	22220	5/8	158	Soft Point	1235	1104	1015	335	328	351	0.2	0.8
	R357M5	22224	5/8	158	Semi-Wadcutter	1235	1104	1015	335	428	361	0.2	0.8
	R357MA	22445	5/8	165	Jacketed Hollow Point Core-Lok™	1281	1237	1109	410	361	318	0.2	0.7
	R357M10	22234	5/8	180	Semi-Jacketed Hollow Point	1374	1353	983	524	543	386	0.2	0.9
	GS357MA	22400	5/8	125	Brass Jacketed Hollow Point	1285	1152	1005	413	368	333	0.2	0.8
38 S&W	R38SM1	22235	1 1/2	115	Jacketed Hollow Point	1155	1047	973	348	280	241	0.8	3.3
	R38SM3	22280	1 1/2	115	Metall Case	1135	1041	973	329	277	242	0.8	4.0
	R38SM4	22292	1 1/2	115	Jacketed Hollow Point - Bonded	1081	1026	1154	428	384	340	0.8	0.7
	R38SM6	22288	1 1/2	115	Jacketed Hollow Point - Bonded	1250	1113	1019	390	316	295	0.2	0.8
	R38SM10	22324	1 1/2	115	Jacketed Hollow Point - Bonded	1280	1178	1113	399	353	318	0.2	0.8
	R38SM12	22440	1 1/2	124	Metall Case	1110	1030	971	381	297	259	0.2	0.9
	R38SM13	22093	1 1/2	124	Jacketed Hollow Point	1123	1067	1027	345	315	280	0.2	0.8
	R38SM14	22299	1 1/2	147	Jacketed Hollow Point - Bonded	990	941	900	320	289	264	0.3	1.1
	GS38SM13	22423	1 1/2	124	Brass Jacketed Hollow Point	1123	1074	1064	348	317	293	0.2	0.9
	GS38SM14	22424	1 1/2	124	Brass Jacketed - Bonded - Bonded - Bonded	1180	1131	1063	365	352	326	0.2	0.8
	GS38SM15	22453	1 1/2	124	Brass Jacketed Hollow Point - Bonded	1183	1133	1089	383	352	335	0.2	0.8
	GS38SM16	22429	1 1/2	147	Brass Jacketed Hollow Point	990	965	941	320	304	289	0.3	1.1
	GS38SM17	22452	1 1/2	147	Brass Jacketed Hollow Point - Bonded	995	995	941	320	304	289	0.3	1.1
380 Auto	R380A1	22246	1 1/2	88	Jacketed Hollow Point	990	920	868	191	165	146	0.3	1.2
	R380A2	22252	1 1/2	95	Metall Case	955	885	785	198	168	148	0.3	1.3
	GS380A2	22410	1 1/2	102	Brass Jacketed Hollow Point	940	920	901	200	192	181	0.3	1.1
38 S&W	R38SW	22205	1 1/2	98	Lead Round Nose	685	650	625	150	135	125	0.6	2.5
38 Special**	R38S10	22291	1 1/2	110	Semi-Jacketed Hollow Point - Bonded	990	920	871	242	210	195	0.3	1.2
	R38S16	22310	1 1/2	110	Semi-Jacketed Hollow Point	990	900	840	220	194	172	0.3	1.3
	R38S2	22262	1 1/2	125	Semi-Jacketed Hollow Point - Bonded	945	890	850	246	224	204	0.3	1.3
	R38S3	22284	1 1/2	148	Lead Round Nose	710	634	585	168	132	105	0.6	2.4
	R38S5	22288	1 1/2	158	Lead Round Nose	795	723	682	200	183	158	0.5	2.1
	R38S11	22391	1 1/2	148	Semi-Wadcutter - Bonded	880	851	823	278	257	236	0.3	1.4
	R38S6	22290	1 1/2	158	Semi-Wadcutter	795	723	682	200	183	168	0.5	2.1
	R38S12	22303	1 1/2	180	Lead Hollow Point - Bonded	880	855	823	278	257	238	0.3	1.4
	GS38S6	22432	1 1/2	125	Brass Jacketed Hollow Point - Bonded	915	910	921	254	250	235	0.3	1.3
38 Short Colt**	R38SC	22368	1 1/2	125	Lead Round Nose	730	686	645	180	150	115	0.5	2.2
357 Sig	R357S1	22266	5/8	125	Jacketed Hollow Point	1350	1245	1157	506	430	372	0.2	0.7
	GS357S1	22403	5/8	125	Jacketed Hollow Point - Bonded	1350	1245	1157	508	430	372	0.2	0.7
40 S&W	R40SW1	22347	5/8	155	Jacketed Hollow Point	1205	1089	1017	480	413	356	0.2	0.8
	R40SW2	22353	5/8	180	Jacketed Hollow Point	1015	960	914	412	369	334	0.3	1.1
	GS40SW1	22440	5/8	155	Brass Jacketed Hollow Point	1150	1089	1040	404	435	396	0.2	0.9
	GS40SW2	22445	5/8	180	Brass Jacketed Hollow Point - Bonded	1153	1089	1040	404	435	396	0.2	0.9
	GS40SW3	22442	5/8	180	Brass Jacketed Hollow Point	1015	966	960	412	368	368	0.3	1.1
	GS40SW4	22443	5/8	180	Brass Jacketed Hollow Point - Bonded	1015	966	960	412	368	368	0.3	1.1
41 Rem Mag**	R41M1	22415	2 1/2	210	Soft Point	1301	1162	1062	786	630	526	0.2	0.7
45 Colt**	R45C1	22463	2 1/2	225	Semi-Wadcutter	960	890	832	480	395	340	0.3	1.3
	R45C2	22490	2 1/2	229	Lead Round Nose	960	890	790	410	375	340	0.3	1.5
40 Auto	R40AP2	22459	2 1/2	180	Jacketed Hollow Point	1090	920	883	411	362	324	0.3	1.1
	R40AP3	22465	2 1/2	230	Jacketed Hollow Point (Subsonic)	835	690	767	356	325	300	0.3	1.6
	R40AP4	22466	2 1/2	230	Metall Case	835	690	787	356	326	300	0.3	1.6
	GS40AP1	22444	2 1/2	185	Brass Jacketed Hollow Point	1015	981	951	423	395	371	0.3	1.1
	GS40AP2	22414	2 1/2	185	Brass Jacketed Hollow Point	1015	981	951	423	395	371	0.3	1.1
	GS40AP3	22445	2 1/2	185	Brass Jacketed Hollow Point - Bonded	1140	1086	1041	434	384	365	0.2	0.9
	GS40AP4	22446	2 1/2	230	Brass Jacketed Hollow Point	875	853	833	398	372	354	0.4	1.5
	GS40AP5	22373	2 1/2	230	Brass Jacketed Hollow Point - Bonded	875	853	833	398	372	354	0.4	1.5

*Note: These ballistics reflect velocity, energy, and trajectory. "P" or "F" on the case headstamp is added to higher pressure this only in firearms designed to fire cartridges and some manufactured by the gun manufacturer. Remington Pistol and Revolver Duty Ammunition is tested at 70 degrees per case.