DISINTEGRATOR' LEAD-FREE, FRANGIBLE, REDUCED HAZARD AND TARGET TRAINING SHELLS

Disintegrator® Lead-Free and Heavy-Metal-Free, Frangible Reduced Hazard Buckshot and Sing Training Shells were developed for realistic, safe, and cost effective training and qualification programs while helping to provide a Reduced Hazard range for students, instructors, and the environment. Nothing's better where training safety, long-term effects, clean up, and environmental concerns are involved.

- High-Strength Metal Particle breaks upinstantly and completely upon iniginal against hard surfaces leaving nothing bas harmless, metal particles.
- Completely Lead-free Buckskin, Stugs, and fleavy-Metal-Free Printing Wilk eliminates lead and recovery issues white scoulding clean, instantaneous ignition.
- Splash-back of Fragments is Virtually Eliminated.
- Duplicates the Felt Recoit, Point-of-Impact, and Groups/Poiterns of the best duly shells.
 Giges the same performance and feer as standard duly rounds for more realistic training.
- Short Cup and Buffering Protect Short for ennanced patterns and new sealer technology ensures no buffer leakage under normal conditions.
- · Shoots Clean for Less Fooling.
- For All Training Situations: standard, close quarter, competition, qualification, or specialty programs.





Buckshot (Lead-Free, Plated, Frangible)

Gauge	index EDI No.	Ramac (fo.	Primer No.	Shell Length	Yelocity (ft./sec.)	Buckshot Size	Pellet Count
12	£F12800	24039	308 Heavy Motor Ricc	934	1600	00	
12	£F129B90	5 th 02	SUSTRIACTED SECTION	, 234"	1550	90	3
12		26038	209 Hearly Method see		1/150	::::::::::::::::::::::::::::::::::::::	27
12 (Reduced Recoil)	RRUF: 2000	80833	See 209 Hoavy Military Free	5 84.	1300	90)	54 8 .1, 64, 65
12 (Reduced Recoil)	HRU 129000	20641	208 J kavy Metal Fres	2 kr	1250	00	
12 (Reduced Recoil)	BRLF1284	<u>}}2</u> 9617	20% Neavy-Metal-Free	2 %/"	1200	4	27

Bleckshof in peckaged 250 carrest per cisca

Sabot Slugs (Lead-Free, Frangible)

	iadex	Barnac Printer Shell		Shell	Sing Wt.	. Velocity (ft./sec.)				Energy (ft./lbs.)				Mid-Range Trajectory (in.)			
Cauge	EDI No.	No.	and the same	Length	(oz.)	Muzzle	25 yds.	50 yds.	100 yds.	Muzz te	25 yds.	50 yds.	100 yds.	25 yds.	50 yds.	100 yds.	. :
32000	1F12F8\$	20807	四角化		8886.74	3815	3476	1203	!K#\$	1997	1310	877	533	0.1	11.5	3.0	. :
12 (Reduced Recoil)	RPLF12FSS	20649:	209 Hr	250	838888	1,700	1377	15.40	911	1752	1149	788	503	0.1	0.6	3.3	

III = Heavy-Metal-Tree — Sahot Slug is packaged \$50000000000000000

Premier® STS® Target Training Sticils ##Great familiarization birdshot training loads available in five birdshot sizes: 7, 7, 1/2, 8, 8, 1/2, and 9. The STS12LFS7 utilizes stess shot and a Heavy-Metal-Free primer.

Remington® Target Shotshells

	.+ I	.4500000		775		Oram.	Velocity	Gunnoes	Short	Rounds	Boxes	Bounds
Gaug	P	Index Kill No.	Dames i	k. Gauge	Sheli Length	Egativ.	(ft./sec.)	of Shot	Site	Per Box	Per Case	Per Cose
lause	t Loads	\$18.2.7	\$0130	ž., 12	2 %,"	2 %	\$1 4 5	1 1/6	71/2	25	10	250
mud Må	áng (86)	SFS 2.8	20132	333. 12	27/"	- 2%	1145	9	. 8	25	30.00	250
		SSTS 2185	201 34	5000	: . Lacarra 2 % (acarra)	2.00.2%	1145	: (85	25	36	250
		371S: 2.9	201 競	32	·:	21/4	1145	1 %	9	25		250
000000000000000000000000000000000000000	3 - 2022/11/22	\$1833 HZ	30250	32	· · · · · · · · · · · · · · · · · · ·	3 0000	¥2 00	of the early Means that		25	{	256
	S	31372 in	26232	32	2.70	3. 11	1200	10.86	6	25	100	290
	3 - 3 3 3	5153219	30254	12	2 1/4"	3	1200)	9	25	30	250
		STS (2LFS)*	266	15	2 %/40	3	1200	1 1 Vk		25	10	250

Seed onclean feed-free United