

RIFLE DUTY AND TRAINING AMMUNITION

Remington Centerfire Rifle Cartridge Ballistics (Packed 200 Rounds Per Case)

Caliber	Index EDI No.	Range No.	Primer No.	Wt. Gr.	Bullet Style	Velocity (ft./sec.)		Energy (ft./lbs.)		Short-Range Trajectory (in.)							
						100 yds.		200 yds.		Bullet does not rise more than 1" above line of sight from muzzle to sighting in range.							
						Muzzle	100 yds.	Muzzle	200 yds.	50 yds.	100 yds.	150 yds.	200 yds.	250 yds.	300 yds.		
.22 Rem.	PR-22300	29131	7 1/2	80	Accu-Point Ball Lead	3300	2890	2250	1850	0.2	7.1	0.0	0.0	2.0	1.7	4.8	9.1
	PR-22300C	29132	7 1/2	55	Accu-Point Ball Lead	3240	2854	2200	1800	0.2	7.0	0.0	0.0	2.0	1.6	4.7	8.9
	122301	29133	7 1/2	58	PSP SP	3240	2797	2200	1800	0.2	7.0	0.0	0.0	2.0	1.6	4.7	8.9
	122302	29134	7 1/2	55	Hi-Power Lead	3240	2773	2200	1800	0.2	6.9	0.0	0.0	2.0	1.5	4.6	8.7
	122305	29135	7 1/2	58	Hi-Power Lead	3240	2790	2200	1800	0.2	7.0	0.0	0.0	2.0	1.6	4.7	8.9
.243 Rem.	122306	29136	7 1/2	62	Hi-Power Lead	3095	2522	2062	1662	0.2	6.7	0.0	0.0	2.0	1.6	4.7	8.9
	122307	29137	7 1/2	60	Hi-Power Lead	3000	2420	2000	1600	0.2	6.7	0.0	0.0	2.0	1.5	4.6	8.7
	122308	29138	7 1/2	115	Hi-Power Lead	2775	2323	2000	1600	0.2	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	122309	29139	7 1/2	115	Hi-Power Lead	2775	2323	2000	1600	0.2	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	122310	29140	7 1/2	115	Hi-Power Lead	2775	2323	2000	1600	0.2	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem. S&W	122311	29141	9 1/2	115	Hi-Power Lead	2775	2353	2000	1600	0.3	6.8	0.0	0.0	2.0	1.6	4.7	8.9
	PR-30062	29142	9 1/2	115	Hi-Power Lead	2775	2353	2000	1600	0.3	6.8	0.0	0.0	2.0	1.6	4.7	8.9
	PR-30061	29143	9 1/2	115	Hi-Power Lead	2775	2353	2000	1600	0.3	6.8	0.0	0.0	2.0	1.6	4.7	8.9
	PR-30063	29144	9 1/2	115	PSP Core-Lokt Standard	2775	2372	2100	1800	0.3	6.8	0.0	0.0	2.0	1.6	4.7	8.9
	PR-30064	29145	9 1/2	115	SP Core-Lokt	2775	2392	2100	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Win.	PR-30065	29146	9 1/2	160	SP Core-Lokt	2400	1990	1685	1400	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30066	29147	9 1/2	160	SP Core-Lokt	2400	1990	1685	1400	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30067	29148	9 1/2	170	SP Core-Lokt	2200	1800	1610	1210	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30068	29149	9 1/2	170	SP Core-Lokt	2200	1800	1610	1210	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30069	29150	9 1/2	170	SP Core-Lokt	2200	1800	1610	1210	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30070	29151	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30071	29152	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30072	29153	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30073	29154	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30074	29155	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30075	29156	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30076	29157	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30077	29158	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30078	29159	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30079	29160	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30080	29161	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30081	29162	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30082	29163	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30083	29164	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30084	29165	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30085	29166	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30086	29167	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30087	29168	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30088	29169	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30089	29170	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30090	29171	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30091	29172	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30092	29173	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30093	29174	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30094	29175	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30095	29176	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30096	29177	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30097	29178	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30098	29179	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30099	29180	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30100	29181	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30101	29182	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30102	29183	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30103	29184	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30104	29185	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30105	29186	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30106	29187	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30107	29188	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30108	29189	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30109	29190	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30110	29191	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30111	29192	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30112	29193	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30113	29194	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30114	29195	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30115	29196	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30116	29197	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30117	29198	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30118	29199	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30119	29200	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
.30-06 Rem.	PR-30120	29201	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30121	29202	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30122	29203	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30123	29204	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	8.7
	PR-30124	29205	9 1/2	160	Swift-Scoroon	2600	2200	2000	1800	0.1	6.6	0.0	0.0	2.0	1.5	4.6	