

10,000 DRY CYCLE TEST									
MEASURE SAFETY ON / OFF FORCES EVERY 2000 CYCLES AND SIGNS OF WEAR.									
		BOLT OPEN				BOLT CLOSED			
	0 CYCLES	1	2	3	AVG	1	2	3	AVG
CONTROL # 2	SAFE TO FIRE	2.185	2.160	2.170	2.172	2.225	2.220	2.200	2.215
FIRE CONTROL	FIRE TO SAFE	2.055	2.125	2.145	2.108	5.390	5.435	5.475	5.433
	SIGNS OF WEAR	OK							
	2,000 CYCLES	1	2	3	AVG	1	2	3	AVG
CONTROL # 2	SAFE TO FIRE	1.635	1.670	1.710	1.672	1.760	1.820	1.785	1.788
FIRE CONTROL	FIRE TO SAFE	1.600	1.680	1.615	1.632	4.725	4.790	4.735	4.750
	SIGNS OF WEAR	OK							
	4,000 CYCLES	1	2	3	AVG	1	2	3	AVG
CONTROL # 2	SAFE TO FIRE	1.290	1.350	1.295	1.312	1.305	1.385	1.360	1.350
FIRE CONTROL	FIRE TO SAFE	1.310	1.320	1.285	1.305	4.250	4.295	4.245	4.263
	SIGNS OF WEAR	OK							
	6,000 CYCLES	1	2	3	AVG	1	2	3	AVG
CONTROL # 2	SAFE TO FIRE	1.285	1.235	1.220	1.247	1.315	1.335	1.295	1.315
FIRE CONTROL	FIRE TO SAFE	1.325	1.305	1.325	1.318	4.270	4.200	4.275	4.248
	SIGNS OF WEAR	OK							
	8,000 CYCLES	1	2	3	AVG	1	2	3	AVG
CONTROL # 2	SAFE TO FIRE	1.245	1.255	1.310	1.270	1.340	1.340	1.295	1.325
FIRE CONTROL	FIRE TO SAFE	1.310	1.255	1.310	1.292	4.355	4.355	4.280	4.330
	SIGNS OF WEAR	OK							
	10,000 CYCLES	1	2	3	AVG	1	2	3	AVG
CONTROL # 2	SAFE TO FIRE	1.270	1.270	1.245	1.262	1.235	1.225	1.220	1.227
FIRE CONTROL	FIRE TO SAFE	1.315	1.305	1.325	1.315	3.905	4.115	4.030	4.017
	SIGNS OF WEAR	HOLE IN SIDE PLATE WHERE DETENT SPRING GOES SIGNS OF WEAR.							