

Remington Product Proposal

Date 05/16/04NPP# **2005-14**

RAMAC

See Below Page 1

Brief Description: Model 700 XCR (eXtreme Conditions Rifle)Site Assignment: ☒ ILION ☐ MAYFIELD ☐ R & D

Category:

☒ CENTERFIRE ☐ RIMFIRE ☒ ACCESSORYDist Channel: ☒ DOMESTIC☒ INTERNATIONAL☒ AGENCY☐ LAW ENFORCEMENT☐ NTL ACCOUNTSSales Type: ☒ CATALOG ☐ SPRING☐ WINTER☒ SHOW☐ CUSTOMER SPECIALDelivery Info ☒ BEGIN SHIPPING BY12/1/2004☒ SHIP WITHIN THESE DATES05/01/05-07/31/05☐ MULTIPLE P.O. RELEASE DATESProduct Description ☒ NEW☐ REPEAT☐ MODIFYnotes: New "super stainless" line for M700 category that features newBodycote PVD coating, new stock with rubber overmolded panels,R3 pad and hinged floorplate. Guard and floorplate,bbl assmb., bolt assmb. boltplug should all match with coating.Trigger pull weight to be set at final assembly @ 4.5lb - 5.5lbs range.Engineering to provide details on features/benefits of new coating by6/1/04. Engineering should also conduct test to demonstratednew coating's anti-corrosion properties as they compare to Ruger, Browning/USAC, Savageproducts for use by Marketing in promoting the new line.See Trull for details on conducting this testing.Product SpecsModel: 700 XCRHand: RTCaliber: Multiple - See belowStock Material ☐ WOOD ☒ SYNTHETIC ☒ LAMINATEType/Color: New w/ overmolded gripsStock Finish ☐ HIGH GLOSS ☒ MATTE ☐ CAMO ☐ OTHERReceiver Material ☒ STAINLESS ☐ CARBON ☐ STANDARDReceiver Finish ☐ GLOSS ☒ SATIN ☐ BLAST ☐ BLACK OX ☒ BODYCOTE PVD ☐ CAMOBarrel Material ☒ STAINLESS ☐ CARBON ☐ STANDARDBarrel Finish ☐ GLOSS ☒ SATIN ☐ BLAST ☐ BLACK OX ☒ BODYCOTE PVD ☐ CAMOBarrel Profile STD & MAGNUM ☐ FLUTED ☐ PORTEDBarrel Length 24" STD LA & SA CALIBERS, 26" MAGS, 24" W/SIGHTS (.375 H&H, .375 ULTRA MAG CBolt Finish ☐ CHROMED ☐ JERMELED ☐ BLUED ☒ OTHER Bodycote PVDCheckering Rubber overmolded panels in grip & fore end (see model)Recoil Pad/Butt Plr R3Drop at Comb STD BDL SSDrop at Heel STD BDL SSLength of Pull STD BDL SSSwivels STD BDL SSSights None (except on .375 H&H & .375 Ultra Mag - see above)Bases None