

10,000 DRY CYCLE TEST									
MEASURE SAFETY ON / OFF FORCES EVERY 2000 CYCLES AND SIGNS OF WEAR.									
		BOLT OPEN				BOLT CLOSED			
	0 CYCLES	1	2	3	AVG	1	2	3	AVG
A-28	SAFE TO FIRE	2.760	2.625	2.730	2.705	2.795	2.745	2.780	2.773
FIRE CONTROL	FIRE TO SAFE	2.680	2.635	2.645	2.653	5.830	5.875	5.910	5.872
	SIGNS OF WEAR	OK							
		1	2	3	AVG	1	2	3	AVG
A-28	SAFE TO FIRE	2.630	2.640	2.585	2.618	2.590	2.555	2.570	2.572
FIRE CONTROL	FIRE TO SAFE	2.510	2.510	2.535	2.518	5.455	5.485	5.485	5.468
	SIGNS OF WEAR	OK							
		1	2	3	AVG	1	2	3	AVG
A-28	SAFE TO FIRE	2.425	2.370	2.405	2.400	2.485	2.480	2.515	2.497
FIRE CONTROL	FIRE TO SAFE	2.260	2.285	2.245	2.263	5.420	5.555	5.545	5.507
	SIGNS OF WEAR	OK							
		1	2	3	AVG	1	2	3	AVG
A-28	SAFE TO FIRE	2.340	2.280	2.305	2.308	2.495	2.555	2.550	2.533
FIRE CONTROL	FIRE TO SAFE	2.320	2.315	2.330	2.322	5.505	5.525	5.535	5.522
	SIGNS OF WEAR	OK							
		1	2	3	AVG	1	2	3	AVG
A-28	SAFE TO FIRE				#DIV/0!				#DIV/0!
FIRE CONTROL	FIRE TO SAFE				#DIV/0!				#DIV/0!
	SIGNS OF WEAR	DETENT SPRING BROKE 8,000 CYCLES. (PICTURES TAKEN)							
		HOLE IN SIDE PLATE WHERE DETENT SPRING GOES SIGNS OF WEAR.							
		1	2	3	AVG	1	2	3	AVG
A-28	SAFE TO FIRE				#DIV/0!				#DIV/0!
FIRE CONTROL	FIRE TO SAFE				#DIV/0!				#DIV/0!
	SIGNS OF WEAR								

Subject to Protective Order - Williams v. Remington

BARBER 5.30.06R00002579

ETE00000648