Subject to Protective Order - Williams v. Remington

CONFIDENTIAL

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| FA | Fires automatically | | | | | | | |
| FB | Follower binds | | | | | | | |
| FC | Fails to connect | | | | | | | |
| FCB | Fore-end cracked or broken | | | | | | | |
| FD | Follows-down | | | | | | | |
| FF | Fails to fire | | | | | | | |
| FFP | Flat firing pin | | | | | | | |
| FOS | Fires on safe | | | | | | | |
| FPHB | Firing pin hits bbl | | | | | | | |
| FPHI | Firing pin hits inside rim | | | | | | | |
| FPO | Floor plate opens | | | | | | | |
| FPOH | Floor plate opens hard | | | | | | | |
| FSR | Fires when safe is released | | | | | | | |
| FT | Follower tips | | | | | | | |
| GCSO | Gas cyl shot off | | | | | | | |
| HBL | Heavy bolt lift | | | | | | | |
| HMSC | Heading mismatch-steps on case | | | | | | | |
| HPA | High pressure ammo | | | | | | | |
| HUR | Hard under rail | | | | | | | |
| JCS | Jumps cartridge | | | | | | | |
| JM | Jumps magazine | | | | | | | |
| JO | Jars off | | | | | | | |
| LB | Light blow | | | | | | | |
| MAH | Magazine assembles hard | | | | | | | |
| MCW | Magazine capacity wrong | | | | | | | |
| MFA | Misfires (ammo) | | | | | | | |
| MFOP | Magazine follower out of position | | | | | | | |