

GUN #	SERIAL #	LOOSENING TORQUE FRONT SCREW	DEPTH OF FRONT SCREW HOLE	NUMBER OF TURNS TO UNSCREW FRONT SCREW	INSPECT THREADS OF FRONT SCREW	TOTAL LENGTH OF FRONT SCREW
A-1	71154451					
A-2	71154457					
A-3	71163056					
A-4	71163049					
A-5	71163047					
A-6	71163040					
A-7	71154453					
A-8	71163135					
A-9	71163067					
A-10	71163068					
A-11	71163065	34 in lbs	0.0142	1 3/4	OK	1.4390
A-12	71163046	36 in lbs	0.0141	2	OK	1.4395
A-13	71154456	16 in lbs	0.0141	1 7/8	OK	1.4805
A-14	71163149	40 in lbs	0.0139	2	OK	1.4395
A-15	71163138	40 in lbs	0.0139	1 3/4	OK	1.4455
A-16	71163078	35 in lbs	0.0140	1 3/4	OK	1.4405
A-17	71163070	34 in lbs	0.0141	2	OK	1.4445
A-18	71163063	37 in lbs	0.0140	1 3/4	OK	1.4445
A-19	71163147	42 in lbs	0.0139	2	OK	1.4490
A-20	71163151	41 in lbs	0.0141	2 1/4	OK	1.4495
A-21	71163139	30 in lbs	0.0142	1 3/4	OK	1.4405
A-22	71163118	37 in lbs	0.0140	2	OK	1.4380
A-23	71163122	39 in lbs	0.0142	1 3/4	OK	1.4415
A-24	71163071	43 in lbs	0.0142	1 3/4	OK	1.4445
A-25	71163155	38 in lbs	0.0140	2	OK	1.4465
A-26	71163152	38 in lbs	0.0140	1 3/4	OK	1.4415
A-27	71163141	45 in lbs	0.0140	2	OK	1.4460
A-28	71163130	34 in lbs	0.0141	1 3/4	OK	1.4395
A-29	71163125	40 in lbs	0.0141	1 1/2	OK	1.4455
A-30	71163120	35 in lbs	0.0140	1 3/4	OK	1.4435

Subject to Protective Order - Williams v. Remington

BARBER 5.30.06R00006734

ETE00000733