

Product Specs

Model: 40-XS Hand: RT

Caliber: .308 Win

Stock Material ☐ WOOD ☒ SYNTHETIC ☐ LAMINATE Type: McMillan A3 Tactical w/beave

Stock Finish ☐ HIGH GLOSS ☒ MATTE ☐ CAMO ☐ OTHER Green/Black Web

Receiver Material ☒ STAINLESS ☐ CARBON ☐ STANDARD

Receiver Finish ☐ GLOSS ☐ SATIN ☐ BLAST ☐ BLACK OX ☒ POWDER COAT ☐ CAMO

Barrel Material ☒ STAINLESS ☐ CARBON ☐ STANDARD

Barrel Finish ☐ GLOSS ☐ SATIN ☐ BLAST ☐ BLACK OX ☒ POWDER COAT ☐ CAMO

Barrel Profile STD 40-X ☐ FLUTED ☐ PORTED

Barrel Bracket Use Oversized lug from Badger Ordnance (Part #318-018)

Barrel Length 24"

Twist Rate 1:12"

Crown 40-X

Fire Control 40-X

Headspace Must not exceed min + 0.002"

Bolt Finish ☐ CHROMED ☐ JEWELLED ☐ BLUED ☒ OTHER Black Teflon coat

Checkering N/A

Recoil Pad/Butt Plt R3 if we can make it work with McMillan. Not a show stopper if we can't.

Drop at Comb Adjustable

Drop at Heel Adjustable

Length of Pull Adjustable

Swivels STD 700 Police/M-24 configuration (twin front studs, one rear) w/Q.D. swivels

Sling Turner AWS (Part #NMSRAWS Black 50"/52")

Sights None, Clean Barrel (DRILL AND TAP FOR 8-40 THREADS)

Bases Badger Ordnance Steel Picatinny Style

Rings Badger Ordnance Steel

Scope Leupold VXIII 3.5-10x40 LR M1 (30mm tube) (shipped w/Butler Creek flip open covers)

BiPod Harris LM-S Add Pod-Loc From KMW

Special Ser # N/A

Special Markings N/A

Laser Engraving N/A

Special Packaging Pack in Pelican F97092 (Cut Foam to Fit rifle)

Accuracy Specs. Average of (2) 5-Shot Groups not to exceed .75" @ 100yds

Ammunition Req. R308W7

Trigger Guard Sunny Hill all Steel Model

Trigger Guard Trigger Guard should be powder coated or equivalent

Mag Box Use ADL style box attached to receiver (like M-24)

Mag Box Mag box should be powder coated

Mag Capacity 5 Rounds