

(after the student clicks continue)

How to sight in a rifle

(To be written using 'Sighting-In with Remington Extended Range Rifle Ammunition' brochure.
Please let us know if this is the correct information for this section.)

1. Getting Started (to be written)
2. Rough Sighting (to be written)
3. Short-range sighting
4. Long-range sighting
5. Tips for sharper sighting

Loading and Unloading

Please click on each rifle to view the steps involved in the loading and unloading of that particular firearm.

Bolt Action

>>To **LOAD**: chamber and magazine:

1. Point the firearm in a safe direction.
2. Put the safety mechanism in the 'S' position.
3. Raise the bolt handle.
4. Pull the bolt handle all the way back.
5. Push cartridges of the correct caliber, one at a time, into the magazine until it is fully loaded. Keep the bullets aligned toward the chamber.
6. Put one cartridge into the chamber.
7. Use your fingers to push the cartridges in the magazine all the way down. Slowly slide the bolt assembly forward so that the bolt slides over the top of the cartridges in the magazine.
8. Push the bolt handle down.
9. To fire the firearm put the safety in the 'F' position.

Edit Note: Add process for loading with a magazine.

Deleted: four

Deleted: If the firearm is a .300 magnum, you can only load three cartridges. If the firearm is a 17, 222, or 223 caliber, the .300 magazine will hold five cartridges.

Formatted: Highlight

(Do we need to know how to unload models with a floor plate vs. models without a floorplate vs. models with a detachable magazine box? Can we cut this down?)

>>To **UNLOAD**: models with a floor plate:

1. Point the muzzle of the firearm in a safe direction.
2. Put the safety mechanism in the 'S' position.
3. Raise the bolt handle.
4. Put one hand over the top of the ejection port.
5. Slowly pull the bolt handle rearward with your other hand to remove the cartridge from the chamber.