

- E'Town will complete endurance testing on all three firearms.
- Gun cooling cycle will be every 100rds.
- Headspace and trigger pull to be taken at 0 rds., 500rds. and every 1,000rds. during test.
- At 500rds. and every 1,000rds. after, firearm will be cleaned and visually inspected for abnormal wear and indications of cracks.
- Chambers to be cleaned every 500rds.
- Ammunition will be combination of 25% -3" Magnum & 2 3/4" Magnum and 75% - 2 3/4" field loads.
- Three (3) firearms to be tested. All three to 5,000rds each. Continue two to 10,000rds. Note: One for each overall length. (3)

Drop Tests: (E'TOWN)

- Testing to be conducted on three (3) firearms with 0 rounds previous.
- One firearm for each overall length. (3)
- Drop Test procedures to be in complete compliance with S.A.A.M.I. Drops at one foot and four foot, all six positions following S.A.A.M.I. procedures for placement of safety.
- Rotational tests to be conducted also.
- Prior to drop test, gun weight, trigger pull and hammer/sear engagement dimensions to be conducted and recorded.

Intentional Abuse: (ILION or E'TOWN)

- Four (4) firearms to be evaluated.
- Firearms would be subjected to a handloaded charge determined by pressure work-up to be in the range of 51,000psi to 53,000psi.
- This round would be fired in the top barrel of two firearms and the bottom barrel in the others.
- In all cases, photographs of the set-up and results will be taken.