

Subject: Remington Arms Co., Inc.
Bolt Action Centerfire Update Notice

FIREARMS CARE – BOLT ACTION RIFLES

1. Pull the bolt to the rear. Check the chamber to make sure it's empty and not loaded.
2. Open the magazine, or remove if possible. **Make sure the magazine is empty.**
3. Release the bolt stop and remove the bolt. **Refer to the manufacturer's manual for instructions of firearm disassembly.**
4. If the gun has a scope, cap both ends to protect the optics. Never spray cleaners or lubes on a scope.
5. Clean the bore following instructions in your owner's manual. We recommend that you use a plastic bolt guide to protect the trigger assembly during the bore cleaning process.
6. Scrub the breech with a few drops of Rem Oil on a nylon breech brush. For heavy fouling, use a bronze or stainless steel breech brush.
7. Clean the receiver and barrel exterior using patches moistened with Rem Oil.
8. Spray the bolt with Rem Action Cleaner, then scrub with a nylon breech brush, especially the face, locking lugs, and extractor. Finish with a light spray of Rem Oil.
9. After heavy or extended rifle use, remove the stock according to the manufacturer's manual, then spray the trigger assembly, the action, and receiver with a moderate amount of Rem Action cleaner. Brush off dirt and caked lubricants. Wipe clean with patches. Spray lightly with Rem Oil.
10. Reassemble the gun carefully and wipe all metal surface with Rem Oil. Wipe to remove fingerprints and leave a light oil film for rust prevention.

Confidential

6/12/2006

1