

CONFIDENTIAL

Remington Arms Company Inc.
RESEARCH & DEVELOPMENT TECHNICAL CENTER
315 WEST RING ROAD
ELIZABETHTOWN, KY 42701

- Average the 3 trials for each box and at each measurement location.

Data Required:

- Force Measurements taken on each trial per box at each of the measurement locations.
- The Average Force measurement per box.
- The serial number of the Chatillon Digital Force Gauge used for the procedure.

TLW0630AD – Safety Operation (S.A.A.M.I.)

This S.A.A.M.I. required test measures the operation of the manual safety to determine if the force required to move the safety from the “safe” to the “fire” position is less than 1 lb.. In addition, an examination of the safety is made to determine if the “fire” and “safe” position of the safety are clearly discernible to the user. Finally, a 40 lb. load is applied to the trigger from several directions with the safety in the “on” or “safe” position to determine that the mechanical operation of the safety is not impaired.

Method:

- Inspect and verify the rifle is not loaded and the safe is in the “On-Safe” position.
- With the rifle’s safety in the “On-Safe” position, use the Chatillon 10 lb. gauge with a “V” notch attached and carefully push the safety to the “fire” position and measure the force required to move the safety. Perform 3 trials for each rifle and record all three force measurements. These will be averaged to determine the final force measurement for each rifle.
- Make a specific observation as to the position of the “on-safe” and the “fire” and determine if there a discernible “detent” detectable when the safety is moved between the two positions. Record the observation for each sample rifle.
- Finally, lock the rifle securely in a holding device and proceed to apply a 40-lb. load to the trigger. Place the Chatillon 50 lb. gauge v-notch in each of four locations from the front (or as close as you can get from the front.) Then from the rear of the trigger (or as close as you can get from the rear.) Finish by applying the 40 lb. load to the trigger, first from the left side and then from the right side) in turn and apply a 40-lb. load. In each application of the 40-lb. load, placement of the load should be at about the center of the finger curve of the trigger. After each application of the load test the fire control mechanism by attempting to pull the trigger with the safe in the “on-safe” position and the rifle pointed in a safe direction. Gun must not fire. Push the safety to the “fire” position. Gun must not fire when the safety is moved to the “fire” position.

J.R.Snedeker
TLW 0630

Page 16 of 42
Remington Confidential

05/24/06
Revision # 0.3