## CONFIDENTIAL

## Remington Arms Company Inc. Research & Development Technical Center 315 West Ring Road Elizabethrown, KY 42701

- After firing ten rounds the rifle will be checked carefully for the presence of any live ammunition and if
  empty will be placed in the cooling rack. The safety will be in the "On Safe" position and the bolt will be
  unlocked and fully open at all times. Compressed air may be used, if necessary to cool the inside of the
  chamber area if the rifle is excessively hot from firing.
- All malfunctions will be recorded on the data sheets.

## Data Required:

- Rifle serial number
- Tester's name
- Date of test firing
- The TLW#
- The ammunition used for the test with the ammo code number of the rounds actually used.
- Any malfunctions noted or other unusual items of note.

## TLW0630R - Extended Function & Endurance (Do This Test on the Stainless Version):

This Extended Function & Endurance Test will be shot to determine an estimate of the product's expected malfunction rate over an extended period of shooting. For purposes of definition, a component failure will be one that prevents (or could prevent) the firearm from functioning as intended. These are failures that can be fixed relatively easily by the simple replacement of a part such as could be done by the gun owner using only simple household tools. System failures are defined as failures of a major nature, the extent of which would require specialized tooling or methods to repair not normally available to the average gun owner. Such a repair would be most likely made by a qualified gunsmith or by return to the factory.

This Extended Function & Endurance Test will be shot in the Remington test jacks (heavy configuration). The covers on the "belly-protectors" will be down and in-place for each test shot. Careful monitoring of each test guit is essential to evaluate the malfunction rate for each firearm.

Each rifle will be shot no more than 20 rounds before being put aside for cooling. Compressed air applied to the inside of the chamber will be an acceptable method to assist in the cool-down process.

The test will be performed according to Remington's standard endurance test procedures for centerfire rifle. Rounds for this test will be shot according to the attached schedule.

J.R.Snedeker. Page 26 of 42 05/24/06
TLW 0630 Remington Confidential Revision # 0.3