Subject to Protective Order - Williams v. Remington

CONFIDENTIAL

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| FC | Fails to connect | | | | | | | | | | |
| FCB | Fore-end cracked or broken | | | | | | | | | | |
| FD | Follows-down | | | | | | | | | | |
| FF | Fails to fire | | | | | | | | | | |
| FFM | Fails to feed from magazine | | | | | | | | | | |
| FFP | Flat firing pin | | | | | | | | | | |
| FOS | Fires on safe | | | | | | | | | | |
| FSR | Fires when safe is released | | | | | | | | | | |
| GCSO | Gas cyl shot off | | | | | | | | | | |
| GRSO | Guide ring shot off | | | | | | | | | | |
| HPA | High pressure ammo | | | | | | | | | | |
| HUE | Hard under extractor | | | | | | | | | | |
| ILOP | Int. latch out of position | | | | | | | | | | |
| ILRM | Int. latch ret. Missing | | | | | | | | | | |
| ILSB | Int. latch stud broken | | | | | | | | | | |
| ILSP | Int. latch spring out of position | | | | | | | | | | |
| JL | Jumps latch | | | | | | | | | | |
| JO | Jars off | | | | | | | | | | |
| LB | Light blow | | | | | | | | | | |
| MCSO | Magazine cap shot off | | | | | | | | | | |
| MCW | Magazine capacity wrong | | | | | | | | | | |
| MFA | Misfires (ammo) | | | | | | | | | | |
| MFOP | Magazine follower out of position | | | | | | | | | | |
| MLH | Magazine loads hard | | | | | | | | | | |
| OH | Opens hard | | | | | | | | | | |
| PH | Pulls hard | | | | | | | | | | |
| PSI | Proof stamp illegible | | | | | | | | | | |