Test Lab Work Request Form

Rev.3 -20 April, 2000

Date Submitted: 12-19-02	Tracking #: TLW 1075
Project # : 241359	Engineer: B. Howard

Test Objective: EET test of steel M710 CA DOJ bolt plug.

Test Description:

- 1. Check headspace.
- 2. Shoot 200 rounds each on two guns using heaviest grain weight bullet for .270 and .30-06 calibers.
- 3. Visually inspect bolt plug for signs of excessive wear, cracking, or movement of spring retainer for the first 10 rounds—and every 25 rounds thereafter.
- 4. Check and record headspace.
- 5. Magnaflux bolt plugs and report results. Have Metallurgist send short statement of acceptance or rejection to Brad Howard.
- 6. Check with Brad Howard for confirmation before proceeding to steps 7 & 8.
- 7. Drop test each gun according to standard SAAMI guidelines starting with the least abusive test and then progressing to the most abusive test.
- 8. Intentional overload test fire one sample with intentional overload to determine witness paper penetrations if any.
- 9. Return both samples to Brad Howard.

```````````````````````````````````````	
Resource Usage:	Test Results Required:
Manpower Requirements –	Formal Report: n Data Only: yes
Facility Requirements –	Requested Completion Date: 1-17-03
Paguinad Matarials/Destr/Estriament	(include quantities):
Required Materials/Parts/Equipment (	include quantities):
Test Parts Availability Date: 1-10-03	
Start Date: Test A	ssigned To:
Completion Date:  Report Date: Assign	ment Date:

Subject to Protective Order - Williams v. Remington