Subject to Protective Order - Williams v. Remington

CONFIDENTIAL

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| XHB | Extractor hits bbl | | | | | | | | | | |
| | | | | | | | | | | | |
| HI | High | | | | | | | | | | |
| LO | Low | | | | | | | | | | |
| LEFT | Left | | | | | | | | | | |
| RIGHT | Right | | | | | | | | | | |
| DG | Doesn't Group | | | | | | | | | | |
| FSST | Front sight tipped | | | | | | | | | | |
| RSTT | Rear sight tipped | | | | | | | | | | |
| RSBR | Rear sight base raised | | | | | | | | | | |
| FSTR | Front sight raised | | | | | | | | | | |
| FSTL | Front sight loose | | | | | | | | | | |
| RSTL | Rear sight loose | | | | | | | | | | |
| MGPT-G | Missing parts at target | | | | | | | | | | |
| UNCN-G | Uncoded nonconformity at target | | | | | | | | | | |
| | | | | | | | | | | | |
| AI-P | Assembly incompleye at proof | | | | | | | | | | |
| BC-P | Blows cases at proof | | | | | | | | | | |
| BEB-P | Barrel extension broken at proof | | | | | | | | | | |
| BLP-P | Blanked primer at proof | | | | | | | | | | |
| BP-P | Blown primer at proof | | | | | | | | | | |
| BS-P | Barrel split at proof | | | | | | | | | | |
| DLOS-P | Doesn't lock over shells at proof | | | | | | | | | | |
| ESB-P | Ejector sticks back at proof | | | | | | | | | | |
| FCB-P | Fore-end cracked at proof | | | | | | | | | | |
| FESO-P | Fore-end shot off at proof | | | | | | | | | | |
| FF-P | Fails to fire at proof | | | | | | | | | | |