

TO George Martin
FROM GENC BULLER

SAFETY MALFUNCTIONS
GALLERY

DATE 5-2-75

MODEL	MALFUNCTIONS										TOTAL SAFETY MALFUNCTIONS BY MODEL	
	FSR	JO	FD		FOS		SWW					
40			4								4	
P 100			3								3	
540												
541				2	1						3	
580									1		1	
581			3	2	1						6	
582												
700			10	11	55						140	
800	9		7	19	10						147	
788	4		3	9	3	2	9	4	14	95	53	196
REL HALF TOTALS	14		30	106	70	3	29	24	74	97	53	470

MALFUNCTION MEANINGS

FSR - FIRES WHEN SAFE IS RELEASED - SELF EXPL.

JO - JARS OFF (HAMMER FAILS TO STAY ENGAGED WITH SEAR AND FALLS DOWN WHEN GUN IS JARRED.)

FD - FOLLOWS DOWN (COCKING PIECE FAILS TO PROPERLY ENGAGE WITH SEAR AND FOLLOWS THE COCKING CAM SURFACE OF THE BOLT TO THE FIRED POSITION).

FOS - FIRES ON SAFE (GUN FIRES WITH SAFE IN "ON" POSITION WHEN TRIGGER IS PULLED).

SWW - SAFETY WON'T WORK - SELF EXPL.

010000150

* - 1975 DATA FROM DEC. 26, 1974 TO APRIL 29, 1975 ONLY.

1 : 44