

GUN # A-29

SERIAL # 7100 1214

CAL. 30.06 SPRG.

REMINGTON M/710

TRIAL and PILOT

DAILY TEST DATA SHEET

PROJECT #241095

TLW0300

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JW/BL	11-4-00	PROOF STAMP + MAGNATEX STAMP ✓			
SW/JW/BL	11-4-00	HEAD SPACE	min + .001		
SW/JW/BL	11-4-00	Load Safety Function test	Remington Ammo R30064 (shot 10 Rounds)	10	10
SW/JW/BL	11-4-00	HEAD SPACE	min + .002		
Jesse/BL	11-5-00	POI Relative To POA		5	15
JA/BL	11-5-00	Trigger Pulls	(1) 5.75 (2) 5.75 (3) 5.25 AVERAGE 5.583		
JA/BL	11-5-00	Indent	(1) .018 (2) .018 (3) .018 AVERAGE .018		
JA/BL	11-5-00	Measurements	Sear Trigger Engagement (1) .0297 (2) .0304 (3) .0311 AVERAGE .0304 Sear Lift (1) .0130 (2) .0142 (3) .0143 AVERAGE .0138		
SW	11-5-00	Bolt Stop Function	Test OK Locked position / Unlocked position Bare Hand OK Closed Hand OK		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

ET06801

Confidential - Subject to Protective Order

Williams v. Remington