

CAL. 30.06 SPRG.

REMINGTON M/710 TRIAL and PILOT DAILY TEST DATA SHEET

PROJECT #241095
TLW0300

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JW/BL	11-4-00	PROOF STAMP + MAGNETIC STAMP			
SW/JW/BL	11-4-00	HEAD SPACE	min + .002		
SW/JW/BL	11-4-00	10rd safety function test	Remington Ammo A30064 (shot 10 rounds)	10	10
SW/JW/BL	11-4-00	HEAD SPACE	min + .002		
JA/BL	11-5-00	POI Relative To POA		5	15
JA/BL	11-5-00	Trigger Pulls	(1) 4.15 (2) 4.25 (3) 4.25 AVERAGE 4.33		
JA/BL	11-5-00	Indents	(1) .018 (2) .018 (3) .018 AVERAGE .018		
JA/BL	11-5-00	Measurements	Sear Trigger Engagement (1) .0259 (2) .0265 (3) .0267 Average .0263		
			Sear Lift (1) .0152 (2) .0147 (3) .0145 AVERAGE .0148		
SW	11-5-00	Bolt Stop Function Test	OK Locked position / Unlocked position		
PCR	11-6-00	Returned to	Barre Hand OK Closed Hand OK Mayfield to show trigger in Normal position location relative to Trigger guard.		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

Confidential - Subject to Protective Order

ET06805