

TLW 0010ARProject No. 241095**S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST**

Gun# B-30 Firecontrol Type: standard Date: 9/10/00
 Dry Cycles/Rounds Completed: _____ Stock Type _____ Engagement at Start 0210
 Model No. 710 Serial No. 71001302 Engagement at End 0186
 Trigger Pull at Start of Test (1) 4.0 (2) 3.75 (3) 4.0 (4) 3.75 (5) 3.75 (6) 3.75
 Average Trigger Pull at Start of Test: 3.83 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 3.50 (2) 3.75 (3) 3.50 (4) 3.25 (5) 3.25 (6) 3.25
 Average Trigger Pull at End of Test: 3.42 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SW/JW

Additional Notes and Comments

Gun with scope

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note for Firearms with the ISS system installed - The ISS will be set in the unlocked
 position for all six orientations of the Jar-Off Test

| Orientation | ISS Unlocked | Comments |
|--|---|--------------------------|
| Barrel Vertical, Muzzle Up: | Pass <input checked="" type="checkbox"/> Fail _____ | |
| Barrel Vertical, Muzzle Down: | Pass <input checked="" type="checkbox"/> Fail _____ | |
| Barrel Horizontal, Left side of Stock Up: | Pass <input checked="" type="checkbox"/> Fail _____ | |
| Barrel Horizontal, Right side of Stock Up: | Pass <input checked="" type="checkbox"/> Fail _____ | |
| Barrel Horizontal, Bottom of Stock Up: | Pass <input checked="" type="checkbox"/> Fail _____ | |
| Barrel Horizontal, Bottom of Stock Down: | Pass <input checked="" type="checkbox"/> Fail _____ | <u>Fired Primed Case</u> |

B-30

TLW 0010AQ

Project No. 241095

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST*SAAMI Specifications for Standard Drop Test:*

Drop Test: 48-inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the unlocked position for all six orientations of the Drop Test

| Orientation | ISS Unlocked | Comments |
|--|--|-------------------|
| Barrel Vertical, Muzzle Up: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | |
| Barrel Vertical, Muzzle Down: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | |
| Barrel Horizontal, Left side of Stock Up: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | |
| Barrel Horizontal, Right side of Stock Up: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | |
| Barrel Horizontal, Bottom of Stock Up: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | |
| Barrel Horizontal, Bottom of Stock Down: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | Fired Primed Case |

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
 Drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the unlocked position for both orientations of the Rotation Test.

| Orientation | ISS Unlocked | Comments |
|--|--|-------------------|
| Firearm Vertical, Drop so left side of Stock is Up: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | |
| Firearm Vertical, Drop so right side of Stock is Up: | Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/> | Fired Primed Case |

Notes: (continue on back of sheet if necessary)

Tester's Initials SW/JW

PROJECT # 241095
TLW0010AR
SAAMI JARR-OFF TEST
BY STEVE WADE & JEFF WADE
DATE- 09/10/00

ORIENTATION

| | NUMBER TYPE | GUNS B-24 SIGHTS | B-25 SIGHTS | B-26 SIGHTS | B-27 SCOPE | B-28 SCOPE | B-29 SCOPE | B-30 SCOPE |
|---|----------------|------------------------|----------------|----------------|---------------|---------------|---------------|---------------|
| BARREL VERTICAL, MUZZLE UP | | PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| BARREL VERTICAL, MUZZLE DOWN | | PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| BARREL HORIZONTAL, LEFT SIDE OF STOCK UP | | PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| BARREL HORIZONTAL, RIGHT SIDE OF STOCK UP | | PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| BARREL HORIZONTAL, BOTTOM OF STOCK UP | | PASS | PASS | PASS | PASS | PASS | PASS | PASS |
| BARREL HORIZONTAL, TOP OF STOCK UP | | PASS | PASS | PASS | PASS | PASS | PASS | PASS |

FOR FURTHER INFORMATION PLEASE SEE THE ACTUAL TEST FORMS.

ET07217